



Available on  
**GeM**  
Government  
e Marketplace



# Video/ Data Wall

*For clear bright Pictures and Videos*



- GL-55HN01
- GL-55HN02

**★ Advanced Feature**

LCD Technology with LED Backlit


24 x 7 Continuous Operation

Intelligent Cooling System

Video Wall Configuration (Upto 10 x 10)

Temperature Sensor

1 2  
3 4 5



# Specifications

## Video / Data Wall Display



Model	GL-55HN01	GL-55HN02
Panel Size	55 Inch	
Splicing Seam (Bezel to Bezel)	3.5 mm	1.8mm
Thickness of display	< 200 mm	
Resolution	1920 x 1080p	
Display Color	1 GB (10 bit)	
Backlit	LED	
LED Life	50,000 Hrs	
Aspect Ratio	16:9	
Response Time	8 ms	
Contrast Ratio	2000:1	
Brightness	500 cd/m <sup>2</sup>	700 cd/m <sup>2</sup>
Signal Format	NTSC, PAL, 480P, 576P, 720P, 1080I, 1080P	
Viewing Angle	178°/178° (H/V)	
Control Interface	IR remote controller and RS232	
Connectivity	VGA, DVI, Display Port, HDMI-1, HDMI-2, Stereo Mini-Jack, DVI-D, USB	
Operating Temperature	0°C to 40°C	
Storage Temperature	20°C to 60°C	
Humidity	10% to 80% (relative)	
Power Supply	AC110V - AC220V ± 10%	
Power Consumption (Max.)	220W	250W
Weight	27.5 Kgs	
Dimension (Length x Width x Thickness)	1213.4 x 684.2 x 115 mm	
Accessories	User Manual, Software CD, Power Cord, Remote Controller	

*\*Due to continuous product development, the specifications may change without prior notice.*

*\*\*Product image(s) are for illustrative purposes only and may differ from the actual product.*

### For Sales

Contact: +91 8588839434 Email: sales@globusinfocom.com



### Globus Infocom Ltd.

C -1/2, Safdarjung Development Area, New Delhi - 110016

E-mail: info@globusinfocom.com, Website: www.globusinfocom.com

Toll Free: 1800-200-4398



Available on  
**GeM**  
Government  
e Marketplace

