

# “A Promising Tool to Give An Exhilarating Experience in Presentations”

PERFECT PICTURE PROJECTION  
↑



Lamp Life: 6000Hrs.

GD30S / GD30X

- › Auto Image Keystone Correction
- › Auto Ceiling Image Reverse
- › Auto Source Selection
- › Digital Zoom
- › Top Loading Lamp Replacement


## Product Specifications

FEATURE	GD30S	GD30X
Native Resolution	800 x 600 (SVGA)	1024 x 768 (XGA)
Brightness	3000 Lumens	
Contrast Ratio	3000 : 1	
Lamp	230W	
Video Compatibility	NTSC 4.43, PAL-M, PAL-N, DTV, HDTV(480i, 480p, 575i, 575p, 720p, 1035i & 1080i)	
Input Compatibility	VGA, SVGA, XGA, SXGA, WXGA, UXGA, MAC	
Projection Size	40" ~ 300"	
Aspect Ratio	4:3 / 16:9	
Speaker	10Watts	
Input/Output Communication Ports	VGA x 1, S-Video x 1, Mini Jack (Stereo IN) x 1, RCA (L/R) x 1, Mini Jack (Audio OUT) x 1, RS-232C x 1, USB x 1	
Lamp Life	6000 Hrs. (Eco Mode) & 3000 Hrs. (Normal Mode)	
Lamp Hour Counter	Built-in	
Remote	Full Functional Remote Control	
Power Supply	100 - 240V AC, 50/60 Hz, ±10%	
Power Consumption	280 Watts	
Operating Temperature	0°C to 50°C, 90% RH	
Optional Accessories	Interactive Display Module	
Special Features	Auto Digital Keystone Correction Auto Ceiling Image Reverse Auto Source Selection Digital Zoom Top Loading Lamp Replacement	

*\*Due to continuous development, the specifications may change without any prior notice*



GD30S / GD30X



An ISO 9001:2008 Company

### Globus Infocom Ltd.

A-22, Sector-4, Noida - 201301

District Gautam Budh Nagar (Uttar Pradesh) INDIA

Tel: +91-120-4051700, 4051800, Fax: +91 - 120 - 4051726

Email: sales@globusinfocom.com, Website: www.globusinfocom.com

**Toll Free**  
1800-200-4398