

GLOBUS ULTRA SERIES PROJECTORS

PERFORM WITH EXCELLENCE WITH OUR NEW ULTRA SERIES PROJECTORS

- Auto Image Keystone Correction
- Auto Ceiling Image Reverse
- Auto Source Solution
- Digital zoom
- Top Loading Lamp Replacement



ULTRA X25U / X30U



ULTRA X35U / X40U



Ultra Series

Globus Ultra Series Specifications

FEATURE	Ultra X25U	Ultra X30U	Ultra X35U	Ultra X40U
Native Resolution	1024 x 768 (XGA)			
Brightness	2500 Lumens	3000 Lumens	3500 Lumens	4000 Lumens
Contrast Ratio	2500 : 1			
Lamp	230W NSH			
Aspect Ratio	4:3 / 16:9			
Video Compatibility	NTSC 4.43, PAL-M, PAL-N, DTV, HDTV(480i, 480p, 575i, 575p, 720p, 1035i & 1080i)			
Input Compatibility	VGA, SVGA, XGA, SXGA, WXGA, UXGA, MAC			
Projection Size	40" ~ 300"			
Speaker	10Watts			
Input / Output / Communication Ports	VGA x 1, S-Video x 1, Mini Jack (Stereo IN) x 1, RCA (L/R) x 1 Mini Jack (Audio OUT) x 1, RS-232C x 1			
Lamp Life	6000 Hrs. (Eco Mode) & 4000 Hrs. (Normal Mode)			
Lamp Hour Counter	Built-in			
Remote	Full Functional Remote Control			
Power Consumption	280 Watts			
Power Supply	100 - 240V AC, 50/60 Hz, ±10%			
Operating Temperature	0°C to 50°C, 90% RH			
Optional Accessories	Interactive Display Module			
Special Features	Auto Digital Keystone Correction Auto Ceiling Image Reverse Auto Source Selection Digital Zoom Top Loading Lamp Replacement			

**Due to continuous development, the specifications may change without any prior notice*



Toll Free
1800-200-4398



Globus Infocom Ltd.

A-22, Sector-4, NOIDA - 201301,

Gautam Budh Nagar, Uttar Pradesh

Tel: 0120-4051700/800, Fax: 0120-4051724/726

E-mail: sales@globusinfocom.com, Website: www.globusinfocom.com