



Multimedia Projector

Ideal for Interactive Multimedia display in Small to Medium size Classroom, Meeting Room, Laboratories & other locations without the use of expensive electronic Whiteboards.



★ Advanced Feature



Make Any Surface Interactive With Projector And Pen



Upto 10,000 Hours Long Lamp Life



22000:1 Contrast Ratio



Instant Restart + HDMI



±40 Degrees Keystone Correction



HD And 3D Compatible



Ultra Portable 1.9 Kg



Ultra X30U+

Specifications

Globus Ultra X30U+

Technology	DLP
Projection Method	Front & Rear Both
Display Color	1.07 Billion Colors
Native Resolution	1024 x 768 (XGA)
Resolution Support	VGA(640 x 480) to UXGA(1600 x 1200)
Brightness	3000 ANSI Lumens
Contrast Ratio	22000 : 1
Lamp Life (Modes)	5000 Hrs. (Normal), 10000 Hrs. (Eco)
Lamp Wattage	190W
Zoom	1 : 1.1
Video Compatibility	NTSC 4.43, PAL-M, PAL-N, DTV, HDTV(480i, 480p, 576i, 720p, 1080i & 1080p)
Input Compatibility	VGA x 2, SVGA, XGA, SXGA, WXGA, UXGA, Mac
Projection Size	36" ~ 300"
Throw Ratio	1.86 ~ 2.04
Aspect Ratio	4:3 / 16:9 (5 aspect ratio selectable)
Speaker	2W Mono
Input	VGA, HDMI, Mini Jack (Audio), RCA, S-Video
Output	VGA, Mini Jack (Audio)
Control Ports	RS232, USB
Keystone Adjustment	Automatic & Manual Both (ID, Vertical +/- 40 degrees)
Horizontal Frequency	15~102 KHz
Vertical Scan Rate	23~120 Hz
3D Support & Compatibility	Frame Sequential - upto 720p, Frame Packing - upto 1080p, Side by Side - upto 1080i/p
Interactive Feature	Self contained interactive white board functionality including interactive pen & software
Annotation Features	Choose, Pens, Annotate, Erase, Colours, Shapes, Sizes, Text, Edit, Fonts, Stamp, Move, Capture, Picture, Video, Save, Rotate, Undo, Image Gallery, Print, Floating Key-Board and Background etc.
Power Consumption	270W
Audible Noise	2/ 28 dBA (Sleep Mode/ Normal Mode)
Application Modes	Dynamic / Presentation / sRGB / Cinema / 3D / User 1 / User 2
Lamp Hour Counter	Built-in
Remote	Full Functional Remote Control
Power Supply	100 - 240V, 50/60 Hz AC
Operating Temperature	0°C to 40° C, 90% RH
Weight	1.9 kg
Accessories	Lens Cover, Remote Control with battery, Power Cord, Quick Start Guide, VGA Cable, Warranty Card

***Due to continuous product development, the specifications may change without prior notice.**

****Product image(s) are for illustrative purposes only and may differ from the actual product.**

For Sales

Contact: +91 8588839434 **Email:** sales@globusinfocom.com



Globus Infocom Ltd.

A-22, Sector-4, NOIDA - 201301

District Gautam Budh Nagar (Uttar Pradesh) INDIA

Tel: +91-120-4051700, 4051800, Fax: 0120 - 4051827 / 726

E-mail: info@globusinfocom.com, Website: www.globusinfocom.com



**TOLL FREE
1800-200-4398**

