

# CCTV SOLUTIONS


1.3 MP IR bullet camera  
30 Mtrs.



CP-UNC-B

## Features

- 1/3", 1.3MP Image Sensor
- Digital Signal Process
- 2.7~12mm lens
- Max 25fps
- H.264/MJPEG Video Compression and JPEG Image Capture
- Support Alarm I/O
- Remote system update over network using web client.
- Remote administration using web based tools





## IR Bullet Camera

# Specifications

Model: CP-UNC-B

<b>Image Device</b>	1/3", 1.3MP Image Sensor
<b>Signal System</b>	PAL
<b>Effective Pixels/ Resolution</b>	1.3 MP
<b>Frame Rate</b>	25 FPS in all resolution
<b>Compression</b>	H.264 / H.264-B / MJPEG / MPEG 4
<b>Streaming</b>	Dual Compressed stream
<b>Audio</b>	Full Duplex, Audio Input/Output 1 Ch
<b>Alarm</b>	1 Digital Input, 1 Relay Output
<b>Audio Compression</b>	G.726 / G.711
<b>Pre/ Post Alarm Buffer</b>	Available
<b>ID / Password</b>	Multi level user ID / Password
<b>Encryption</b>	HTTP (SSL/TSL)
<b>Protocol</b>	TCP/IP, HTTP, RTP, RTSP, UDP
<b>IP Support</b>	Static & Dynamic both
<b>IR</b>	Available, IR range of 30 mtrs.
<b>Remote Administration</b>	Remote Configuration and status using web based tool
<b>System Update</b>	Remote system update over Network using web client
<b>PC Client</b>	PC application client with a channel recording feature support
<b>Web Client</b>	Viewer through HTTP(minimum) System Configuration Setting / Streaming
<b>Simultaneous Connection</b>	10 Users
<b>noise ratio</b>	> 50 dB
<b>Auto Exposure</b>	Auto, Low Noise, Low Motion Blur, Manual, Anti Flicker
<b>Minimum Illumination</b>	0.01 Lux
<b>Operating Temperature</b>	-10 to 50 degrees Celcius, 40 Deg at 95% RH
<b>Power Source</b>	DC12V/AC24V, PoE
<b>Power Consumption</b>	Max 6W
<b>Regulatory</b>	CE, FCC and RoHS
<b>Signal Process</b>	Digital Signal Process
<b>Motion Detection Zones</b>	4 zones
<b>Auto Gain Control</b>	Available
<b>Back Light Compensation</b>	Available
<b>Electronic Shutter</b>	1/3(4) ~ 1/10000
<b>White Balance</b>	Available
<b>Day and Night</b>	Auto, Day & Night
<b>Iris Control</b>	Available
<b>Mounting Bracket</b>	Wall Mount
<b>Housing Indoor</b>	Plastic / Aluminium Construction
<b>On Screen Display</b>	OSD on Monitor/ Display Unit in English

*\*Due to continuous product development, the specifications may change without prior notice.*

*\*\*Product image(s) are for illustrative purposes only and may differ from the actual product.*

### For Sales

**Contact:** +91 8588839434 **Email:** sales@globusinfocom.com



### Globus Infocom Ltd.

A-22, Sector-4, NOIDA - 201301

District Gautam Budh Nagar (Uttar Pradesh) INDIA

Tel: +91-120-4051700, 4051800, Fax: 0120 - 4051827 / 726

E-mail: info@globusinfocom.com, Website: www.globusinfocom.com

**TOLL FREE**  
**1800-200-4398**

