

CCTV SOLUTIONS

Vandal Proof IP Dome Camera
1.3 MP - Outdoor



CP-UNC-DV-O

★ Features

- 1/3" 1.3 MP Image Sensor
- H.264/MJPEG Video Compression and JPEG Image Capture
- Max 25 FPS @1.3MP
- Dual Encoding Streams Supported
- 2.7-12mm Varifocal Lens
- IR Range of 30 Mtrs., IP 66





Vandal Proof IP Dome Camera - Outdoor

Specifications

Model: CP-UNC-DV-O

Image Device	1/3", 1.3MP Image Sensor
Signal System	PAL
Effective Pixels / Resolution	1.3 MP
Frame Rate	25 FPS in all resolution
Shutter Speed	Auto/Manual, 1/3(4)~1/100000s
Compression	H.264 / MJPEG / H.264-B / MPEG 4 Pt II
Streaming	Dual Compressed stream
Audio	Full Duplex, Audio Input/Output 1 Ch
Alarm	1 Digital Input, 1 Relay Output
Audio Compression	G.726 / G.711
Pre/ Post Alarm Buffer	Available
ID / Password	Multi level user ID / Password
Encryption	HTTP (SSL/TSL)
Protocol	TCP/IP, HTTP, RTP, RTSP
IP Support	Static & Dynamic
Remote Administration	Remote Configuration and status using web based tool
System Update	Remote system update over Network using web client
PC Client	PC application client with a channel recording feature support
Interface	RJ-45 (10/100Base-T) & Rs485
Web Client	Viewer through HTTP(minimum) System Configuration Setting / Streaming
Simultaneous Connection	10 Users
Lens Type	2.7~12mm Verifocal
Signal to noise ratio	> 50 dB
Auto Exposure	Electronic level control, Automatic level control
IR	Available, IR range of 30 mtrs.
Minimum Illumination	0.1 Lux
Operating Temperature	-10 to 50 degrees Celcius, 40 Deg at 95% RH
Power Source	Suitable DC- 12 volt adaptor & POE
Signal Process	Digital Signal Process
Motion Detection Zones	8 motion detection zones
Auto Gain Control	Available
Back Light Compensation	Available
Electronic Shutter	1/50 ~ 1/10000
White Balance	Available
Physical Layer	10/100 base Tx Ethernet
Day and Night	Auto, Day & Night
Iris Control	Available
Housing Outdoor	Plastic / Aluminium with IP66
Mounting	Pole Mount
On Screen Display	OSD on Monitor/ Display Unit in English

**Due to continuous product development, the specifications may change without prior notice.*

***Product image(s) are for illustrative purposes only and may differ from the actual product.*

For Sales

Contact: +91 8588839434 Email: sales@globusinfocom.com



Globus Infocom Ltd.

A-22, Sector-4, NOIDA - 201301

District Gautam Budh Nagar (Uttar Pradesh) INDIA

Tel: +91-120-4051700, 4051800, Fax: 0120 - 4051827 / 726

E-mail: info@globusinfocom.com, Website: www.globusinfocom.com

TOLL FREE
1800-200-4398

