

CCTV SOLUTIONS



20x IP PTZ Camera



CP-UNP-28W-O

★ Features

- 1/3", 1.3MP Image Sensor
- Powerful 20x optical zoom and 16x digital zoom
- H.264 & Dual-stream video encoding and JPEG image capture
- 25 fps in all Resolution
- Day/Night (ICR), Ultra DNR, Auto iris, Auto focus
- 0 deg to 360 deg, max 240 deg per second
- Build-in 2/1 channel alarm input/output
- IR Range of 100 Mtrs., IP 66
- Built-in Web server, CMS(DSS/ PSS), DMSS, NVR





Specifications

Model: CP-UNP-28W-O

| | |
|------------------------------|---|
| Image Device | 1/3", 1.3MP Image Sensor |
| Signal System | PAL |
| Effective Pixels/ Resolution | 1.3 MP |
| Lens Type | 20X optical & 16X digital |
| Signal to noise ratio | > 50 dB |
| Auto Exposure | Auto, Manual, IRIS Priority, Shut Priority |
| Minimum illumination | 0.01 Lux |
| Signal Process | Digital Signal Process |
| Auto Gain Control | Available |
| BLC | Auto, ON, Off |
| Electronic Shutter | 1/50 - 1/10000 |
| White Balance | Available |
| Privacy Zones | 24 privacy Zones |
| Day and Night | Auto, Day & Night |
| Iris Control | Available |
| Alarm input | 2 Input |
| Alarm Output | 1 Output |
| Focus Mode | Auto, manual, Semi-Auto |
| Panning Range and Speed | 0 deg to 360 deg, max 240 deg per second |
| Tilting Range and Speed | 0 to 5 deg above horizontal to 90 deg down, max 120 deg per second |
| Presets | 255 presets |
| Dome ID | 256 Dome ID |
| Group Touring | 8 Groups |
| Frame rate | 25 fps in all resolutions |
| Compression | H.264 / MJPEG / H.264-B / H.264-H |
| Streaming | Dual Compressed stream |
| Pre/ Post Alarm Buffer | Available |
| IR | Available, IR range of 100 mtrs. |
| ID / Password | Multi Level user ID / Password |
| Encryption | HTTP (SSL / TSL) |
| Physical layer | 10/100 base Tx ethernet |
| Protocol | TCP/IP, HTTP, RTP, RTSP |
| IP Support | Static & Dynamic both |
| Remote Administration | Remote Configuration and status using web based tool |
| System Update | Remote system update over Network using web client |
| PC Client | PC application Client with a Channel |
| Web Client | Viewer through HTTP (minimum) System configuration setting/ streaming |
| Simultaneous Connection | 20 users |
| Operating Temperature | -10 to 50 degrees Celcius, 40 Deg at 95% RH |
| Power Source | AC/DC - Power Adaptor Supplied |
| On Screen Display | OSD on Monitor/Display Unit in English |
| Housing Outdoor | Plastic/ Aluminium with IP66 |
| Mounting Bracket | Pole Mount |

**Due to continuous product development, the specifications may change without prior notice.*

***Product image(s) are for illustrative purposes only and may differ from the actual product.*

For Sales

Contact: +91 8588839434 Email: sales@globusinfocom.com



Globus Infocom Ltd.

A-22, Sector-4, NOIDA - 201301

District Gautam Budh Nagar (Uttar Pradesh) INDIA

Tel: +91-120-4051700, 4051800, Fax: 0120 - 4051827 / 726

E-mail: info@globusinfocom.com, Website: www.globusinfocom.com



TOLL FREE
1800-200-4398