

CCTV SOLUTIONS


2 MP Full HD IR bullet camera
30 Mtrs.



CP-UNC-B-H-HD

Features

- 1/3" CMOS, 2MP Image Sensor
- Digital Signal Process
- 2.7~12mm Varifocal Motorized lens
- 25 FPS in all resolutions
- H.264/MJPEG/H.264-B/H.264H Compression
- Day/Night(ICR), Auto Iris, 3DNR, AWB, AGC, BLC
- IR Range of 30 Mtrs., IP66
- Remote system update over network using web client.
- Remote administration using web based tools



2 MP Full HD IR bullet camera - 30 Mtrs.

Specifications

Model: CP-UNC-B-H-HD

Image Device	1/3" CMOS, 2MP Image Sensor
Effective Pixels/ Resolution	2 MP / 1920x1080
Frame Rate	25 FPS in all resolution
Compression	H.264/MJPEG/H.264-B/H.264H
Streaming	Dual compressed stream with H.264
Audio	Full Duplex, Audio Input/Output 1 Ch
Alarm	1 Digital Input, 1 Relay Output
Audio Compression	G.726 / G.711
Pre/ Post Alarm Buffer	Available
ID / Password	Multi level user ID / Password
Encryption	HTTP (SSL/TSL)
Protocol	TCP/IP, HTTP, RTP, RTSP, UDP
Ethernet	RJ45(10/100 Base-T)
IP Support	Static & Dynamic both
Lens	2.7-12mm Varifocal Motorized
IR	Available, IR range of 30 mtrs.
Remote Administration	Remote Configuration and status using web based tool
System Update	Remote system update over Network using web client
PC Client	PC application client with a channel recording feature support
Web Client	Viewer through HTTP(minimum) System Configuration Setting / Streaming
Simultaneous Connection	10 Users
noise ratio	> 50 dB
Auto Exposure	Auto, Low Noise, Low Motion Blur, Manual, Anti Flicker
Minimum Illumination	0.01lux without IR & 0 lux with IR
Operating Temperature	-10 to 50°C, 40°C at 95% RH
Power Source	DC12V/AC24V, PoE
Power Consumption	Max 6W
Regulatory	CE, FCC and RoHS
Signal Process	Digital Signal Process
Motion Detection Zones	4 zones
Privacy Zones	24 Privacy Zones
Auto Gain Control	Available
Back Light Compensation	Available
ONVIF	Available
Electronic Shutter	1/50 ~ 1/10000
Focus Adjustment Analytics	Auto-back focus
White Balance	Available
Wide Dynamic Range	Available
Day and Night	Auto, Day & Night
Iris Control	Available
Mounting Bracket	Pole Mount
Housing Outdoor	Plastic/Aluminum Construction with IP-66 with heater, blower and sun-Shield in built
On Screen Display	OSD on Monitor/ Display Unit in English

**Due to continuous product development, the specifications may change without prior notice.*

***Product image(s) are for illustrative purposes only and may differ from the actual product.*

For Sales

Contact: +91 8588839434 Email: sales@globusinfocom.com



Globus Infocom Ltd.

A-22, Sector-4, NOIDA - 201301

District Gautam Budh Nagar (Uttar Pradesh) INDIA

Tel: +91-120-4051700, 4051800, Fax: 0120 - 4051827 / 726

E-mail: info@globusinfocom.com, Website: www.globusinfocom.com



TOLL FREE
1800-200-4398