

CCTV SOLUTIONS



2.0 Megapixel Full HD Vandal-proof IP Dome Camera - Outdoor



CP-UNC-DV-O-HD

Features

- 1/3" 2.0 MP CMOS Image Sensor
- H.264/MJPEG/H.264-B/H.264H Compression
- 25 FPS in all resolutions
- Day/Night(ICR), 3DNR, AWB, AGC, BLC
- 2.7~12mm varifocal lens
- IR Range of 30 Mtrs., IP 66
- Dual Encoding Streams Supported
- Built-in Web server, CMOB & KVMS(CMS)



2.0 Megapixel Full HD Vandal-proof IP Dome Camera - Outdoor

Specifications

Model: CP-UNC-DV-O-HD

Image Device	1/3", 2MP CMOS Image Sensor
Resolution	1920 x 1080
Frame Rate	25 FPS in all resolution
Compression	H.264 / MJPEG / H.264-B / MPEG 4 Pt II
Streaming	Dual Compressed stream (with H.264)
Audio	Full Duplex, Audio Input/Output 1 Ch
Alarm	1 Digital Input, 1 Relay Output
Audio Compression	G.726 / G.711
Pre/ Post Alarm Buffer	Available
ID / Password	Multi level user ID / Password
Encryption	HTTP (SSL/TSL)
Protocol	TCP/IP, HTTP, RTP, RTSP
IP Support	Static & Dynamic
Remote Administration	Remote Configuration and status using web based tool
System Update	Remote system update over Network using web client
PC Client	PC application client with a channel recording feature support
Web Client	Viewer through HTTP(minimum) System Configuration Setting / Streaming
Simultaneous Connection	10 Users
Lens Type	2.7~12mm Verifocal Motorized
IR	Available, IR range of 30 mtrs.
Signal to noise ratio	> 50 dB
Auto Exposure	Electronic level control, Automatic level control
Minimum Illumination	0.01lux without IR & 0 lux with IR
Operating Temperature	-10 to 50°C, 40°C at 95% RH
Power Source	Suitable DC- 12 volt adaptor & POE
Signal Process	Digital Signal Process
ONVIF	Available
Wide Dynamic Range	Available
Focus Adjustment Analytics	Auto-back focus
Motion Detection Zones	4 motion detection zones
Privacy Zones	24 Privacy Zones
Auto Gain Control	On / Off
Back Light Compensation	On / Off
Electronic Shutter	1/50 ~ 1/10000
White Balance	Available
Physical Layer	10/100 base Tx Ethernet
Day and Night	Auto, Day & Night
Iris Control	Available
Housing Outdoor	Plastic/Aluminum Construction with IP-66 with heater, blower and sun-Shield in built
On Screen Display	OSD on Monitor/ Display Unit in English

**Due to continuous product development, the specifications may change without prior notice.*

***Product image(s) are for illustrative purposes only and may differ from the actual product.*

For Sales

Contact: +91 8588839434 **Email:** sales@globusinfocom.com



Globus Infocom Ltd.

A-22, Sector-4, NOIDA - 201301

District Gautam Budh Nagar (Uttar Pradesh) INDIA

Tel: +91-120-4051700, 4051800, Fax: 0120 - 4051827 / 726

E-mail: info@globusinfocom.com, Website: www.globusinfocom.com



**TOLL FREE
1800-200-4398**