

CCTV SOLUTIONS



30x Full HD IP PTZ Camera



CP-UNP-30W-I-HD

★ Features

- 1/3", 2MP Image Sensor
- Powerful 30x optical zoom and 16x digital zoom
- H.264/MJPEG/H.264-B/H.264H Compression
- 25 FPS in all Resolution
- Day/Night (ICR), Ultra DNR, Auto iris, Auto focus
- 0 deg to 360 deg, max 240 deg per second
- Build-in 2/1 channel alarm input/output
- IR Range of 120 Mtrs.
- Built-in Web server, CMS(DSS/ PSS), DMSS, NVR





Specifications

Model: CP-UNP-30W-I-HD

Image Device	1/3", 2MP Image Sensor
Effective Pixels/ Resolution	2 MP / 1920 x 1080
Lens Type	2.7 to 12 mm Varifocal Motorized
Signal to noise ratio	> 50 dB
Auto Exposure	Auto, Manual, IRIS Priority, Shut Priority
Minimum illumination	0.01lux without IR & 0 lux with IR
Signal Process	Digital Signal Process
Auto Gain Control	Available
Electronic Shutter	1/50 - 1/10000
White Balance	Available
Privacy Zones	24 privacy Zones
Day and Night	Auto, Day & Night
Iris Control	Available
Audio	Full Duplex, Audio Input/Output
Audio Compression	G.726 / G.711
Alarm input	2 Digital Input
Alarm Output	1 Relay Output
Focus Mode	Auto, manual, Semi-Auto
Focus Adjustment Analytics	Auto-back focus
Panning Range and Speed	0 deg to 360 deg, max 240 deg per second
Tilting Range and Speed	0 to 5 deg above horizontal to 90 deg down, max 120 deg per second
Presets	255 presets
Dome ID	256 Dome ID
Group Touring	8 Groups
Frame rate	25 fps in all resolutions
Compression	H.264 / MJPEG / H.264-B / H.264-H
Streaming	Dual compressed stream with H.264
Pre/ Post Alarm Buffer	Available
Focus Adjustment Analytics	Auto-back focus
IR	Available, IR range of 120 mtrs.
Wide Dynamic Range	Available
ID / Password	Multi Level user ID / Password
Encryption	HTTP (SSL / TSL)
Physical layer	10/100 base Tx ethernet
Protocol	TCP/IP, HTTP, RTP, RTSP
IP Support	Static & Dynamic both
Remote Administration	Remote Configuration and status using web based tool
System Update	Remote system update over Network using web client
PC Client	PC application Client with a Channel
Web Client	Viewer through HTTP (minimum) System configuration setting/ streaming
Simultaneous Connection	20 users
Operating Temperature	-10 to 50°C, 40°C at 95% RH
Power Source	24V AC - Power Adaptor Supplied
On Screen Display	OSD on Monitor/Display Unit in English
Housing Indoor	Plastic/Aluminum Construction with IP-66 with heater, blower and sun-Shield in built
Mounting Bracket	Wall Mount Bracket

**Due to continuous product development, the specifications may change without prior notice.*

***Product image(s) are for illustrative purposes only and may differ from the actual product.*

For Sales

Contact: +91 8588839434 **Email:** sales@globusinfocom.com



Globus Infocom Ltd.

A-22, Sector-4, NOIDA - 201301

District Gautam Budh Nagar (Uttar Pradesh) INDIA

Tel: +91-120-4051700, 4051800, Fax: 0120 - 4051827 / 726

E-mail: info@globusinfocom.com, Website: www.globusinfocom.com



TOLL FREE
1800-200-4398