

# CCTV SOLUTIONS



30x Full HD IP PTZ Camera



CP-UNP-30W-O-HD

## ★ Features

- 1/3" CMOS, 2MP Image Sensor
- Powerful 30x optical zoom and 16x digital zoom
- H.264/MJPEG/H.264-B/H.264H compression
- 25 FPS in all Resolution
- Day/Night (ICR), Ultra DNR, Auto iris, Auto focus
- 0 deg to 360 deg, max 240 deg per second
- Build-in 2/1 channel alarm input/output
- IR Range of 120 Mtrs., IP66
- Built-in Web server, CMS(DSS/ PSS), DMSS, NVR



345

## 30x Full HD IP PTZ Camera

# Specifications

Model: CP-UNP-30W-O-HD

|                              |  |
|------------------------------|--|
| Image Device                 | 1/3" CMOS, 2MP Image Sensor  |
| Effective Pixels/ Resolution | 2 MP / 1920 x 1080   |
| Horizontal Resolution        | 1920 x 1080  |
| Lens Type                    | 2.7 to 12 mm Varifocal Motorized   |
| Audio                        | Full Duplex, Audio Input/Output  |
| Audio Compression            | G.726 / G.711  |
| Signal to noise ratio        | > 50 dB  |
| Auto Exposure                | Auto, Manual, IRIS Priority, Shut Priority   |
| Minimum illumination         | 0.01lux without IR & 0 lux with IR   |
| Signal Process               | Digital Signal Process   |
| Auto Gain Control            | Available  |
| Wide Dynamic Range           | 80 dB  |
| Electronic Shutter           | 1/50 - 1/10000   |
| White Balance                | Available  |
| Privacy Zones                | 24 privacy Zones   |
| Day and Night                | Auto, Day & Night  |
| Iris Control                 | Available  |
| Alarm input                  | 2 Digital Input  |
| Alarm Output                 | 1 Relay Output   |
| Focus Mode                   | Auto, manual, Semi-Auto  |
| Panning Range and Speed      | 0 deg to 360 deg, max 240 deg per second   |
| Tilting Range and Speed      | 0 to 5 deg above horizontal to 90 deg down, max 120 deg per second                   |
| Presets                      | 255 presets  |
| Dome ID                      | 256 Dome ID  |
| Group Touring                | 8 Groups   |
| Frame rate                   | 25 fps in all resolutions  |
| Compression                  | H.264 / MJPEG / H.264-B / H.264-H  |
| Streaming                    | Dual compressed stream with H.264  |
| Pre/ Post Alarm Buffer       | Available  |
| Focus Adjustment Analytics   | Auto-back focus  |
| IR                           | Available, IR range of 120 mtrs.   |
| ID / Password                | Multi Level user ID / Password   |
| Encryption                   | HTTP (SSL / TSL)   |
| Physical layer               | 10/100 base Tx ethernet  |
| Protocol                     | TCP/IP, HTTP, RTP, RTSP  |
| IP Support                   | Static & Dynamic both  |
| Remote Administration        | Remote Configuration and status using web based tool                                 |
| System Update                | Remote system update over Network using web client                                   |
| PC Client                    | PC application Client with a Channel   |
| Web Client                   | Viewer through HTTP (minimum) System configuration setting/ streaming                |
| Simultaneous Connection      | 20 users   |
| Operating Temperature        | -10 to 50°C, 40°C at 95% RH  |
| Power Source                 | 24V AC - Power Adaptor Supplied  |
| On Screen Display            | OSD on Monitor/Display Unit in English   |
| Housing Indoor               | Plastic/Aluminum Construction with IP-66 with heater, blower and sun-Shield in built |
| Mounting Bracket             | Pole Mount Bracket   |

\*Due to continuous product development, the specifications may change without prior notice.

\*\*Product image(s) are for illustrative purposes only and may differ from the actual product.

### For Sales

Contact: +91 8588839434 Email: sales@globusinfocom.com



### Globus Infocom Ltd.

A-22, Sector-4, NOIDA - 201301

District Gautam Budh Nagar (Uttar Pradesh) INDIA

Tel: +91-120-4051700, 4051800, Fax: 0120 - 4051827 / 726

E-mail: info@globusinfocom.com, Website: www.globusinfocom.com



TOLL FREE  
1800-200-4398