

# CCTV SOLUTIONS

## Joystick Controller



CP-KBD

### Features

- Three Dimensional Joystick Control of PTZ Functions
- Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Control
- Full HD 1080p live view; Support HDMI & VGA sync output
- Auxiliary Functions
- Network video server
- On-Screen Menu & User Operation Procedure Tips
- External Wi-Fi (Optional)



## Joystick Controller

# Specifications

Model: CP-KBD

Keyboard Keypanel	Electromechanical
Joystick	3-axis, vector-solving, with twisting, return to-center head
Keyboard Connector	RJ-45, RS232, RS485, RS422, USB
Keyboard Communication	Direct Mode, Network Mode
Direct Mode	Interface: RS232/RS485
Network Mode	Interface: RJ45 DVR/Network Dome: IP Address/Port/Protocol
Baud Rates	2400/4800/9600
Resolution	LCD, 75.2mm x 33.85mm
Display	1/4/8/9/16
Power Supply	Power adapter, input 100V~240V 50Hz / 60Hz, output DC12V/1000mA
Power Consumption	5W
Working Temperature	-10 ~ 55 °C
Working Humidity	10%~90%
Atmosphere Pressure	86kpa~106kpa



*\*Due to continuous product development, the specifications may change without prior notice.*

*\*\*Product image(s) are for illustrative purposes only and may differ from the actual product.*

### For Sales

Contact: +91 8588839434 Email: sales@globusinfocom.com



### Globus Infocom Ltd.

A-22, Sector-4, NOIDA - 201301

District Gautam Budh Nagar (Uttar Pradesh) INDIA

Tel: +91-120-4051700, 4051800, Fax: 0120 - 4051827 / 726

E-mail: info@globusinfocom.com, Website: www.globusinfocom.com



TOLL FREE  
1800-200-4398