



Multimedia Projector

Perform with excellence with our new Ultra Series Projectors



Ultra S35U

★ Advanced Feature



Upto 10,000 Hours Long Lamp Life



15000:1 Contrast Ratio



Instant Restart



±40 Degrees Keystone Correction



HD And 3D Compatible



Ultra Portable 1.9 Kg

Specifications

Globus Ultra S35U

Display Color	1.07 Billion Colors
Native Resolution	800 x 600 (SVGA)
Resolution Support	VGA (640 x 480) to UXGA (1600 x 1200)
Brightness	3500 ANSI Lumens
Contrast Ratio	15000 : 1
Lamp Life (Modes)	4500 Hrs. (Normal), 10,000 Hrs. (Eco)
Lamp Wattage	190W
Zoom	1 : 1.1
Video Compatibility	NTSC 4.43, PAL-M, PAL-N, DTV, HDTV(480i, 480p, 576i, 720p, 1080i & 1080p)
Input Compatibility	VGA x 2, SVGA, XGA, SXGA, WXGA, UXGA, Mac
Projection Size	36" ~ 300"
Throw Ratio	1.86 ~ 2.04
Aspect Ratio	4:3 / 16:9 (5 aspect ratio selectable)
Speaker	2W Mono
Input	VGA x 2, Mini Jack (Audio) x 1, RCA x 1, S-Video x 1
Output	VGA x 1, Mini Jack (Audio)
Control Ports	RS232 x 1, USB x 1
Keystone Adjustment	ID, Vertical +/- 40 degrees
Horizontal Frequency	15~102 KHz
Vertical Scan Rate	23~120 Hz
3D Support & Compatibility	Frame Sequential - upto 720p, Frame Packing - upto 1080p, Side by Side - upto 1080i/p
Power Consumption	270W
Audible Noise	33/28 dBA (Normal/Economic mode)
Application Modes	Dynamic / Presentation / sRGB / Cinema / 3D / User 1 / User 2
Lamp Hour Counter	Built-in
Remote	Full Functional Remote Control
Power Supply	100 - 240V, 50/60 Hz AC
Operating Temperature	0°C to 40° C, 90% RH
Weight	1.9 kg
Accessories	Remote Control with battery, Power Cord, Quick Start Guide, VGA Cable, Warranty Card

**Due to continuous product development, the specifications may change without prior notice.*

***Product image(s) are for illustrative purposes only and may differ from the actual product.*

For Sales

Contact: +91 8588839434 Email: sales@globusinfocom.com



Globus Infocom Ltd.

A 65/66, Sector - 4, Noida - 201301 (U.P.)

E-mail: info@globusinfocom.com, Website: www.globusinfocom.com

Toll Free: 1800-200-4398

