



Available on
GeM
Government
e Marketplace



Visualizer

Globus introduces latest range of eco-friendly visualizers



GVP - 301

- Vivid & Convincing Presentation Tool
- Dazzling, incredible Crystal Clear Picture
- Empowers Quality Learning Experience
- Power to Engage & Communicate Effectively
- Displays Books, Photos & 3D Objects

SXGA
1280 x 1024

Frame Rate
30 FPS

High Resolution
700 TV Lines

12
345

Specifications

Stop Watching....

Start Feeling.....!!!!

An Original Look To Any Image

With The New Range Of **Globus-Visualizers**

The **Globus-Visualizer** is the most flexible presentation tool of our times. It can pick-up any kind of material (books, photos, 3-dimensional objects etc.) quickly and easily and provide a high resolution output signal for video/data projectors, monitors, interactive whiteboards or video conferencing systems.

Compared to rather "stiff" PowerPoint presentations, a presentation with a **Globus-Visualizer** is much more flexible and "alive" because anything can be displayed at any time, with no fixed order and without any advance preparation.

The **Globus-Visualizer** enables the presenter to translate ideas into convincing interactive presentations, spontaneously and naturally, and to engage and communicate with an audience in a manner that is more effective than any other presentation method, ensuring that each and every presentation is a memorable experience for the audience.

Features	GVP-301	
CAMERA		
Image pick-up device		1/3" CMOS sensor
Total Pixels		2M pixels
Effective Pixels		1,280(H) x 1,024(V)
Frame Rate		30 fps
Resolution	RGB Output	SXGA (1280 x 1024)
	Aspect Ratio	5:4
	Video Output	700 (H) TV lines
OPTICS		
Optical Zoom		12X
Digital Zoom		13X
Lens		F1.6~3.7, f 3.9~46.8mm
Shooting Area		210 x 297 mm (Landscape)
Focus		Auto/Manual
FUNCTIONS		
Graphics Interface		Provided
Computer Interface		USB with software
Split Screen		Provided
White Balance		Auto/Manual
Negative/Positive Conversion		Provided
SD Card Slot		Provided
Image Memory		128 Images
Mirror Image		Provided
Colour/ B&W Selection		Provided
Freeze (Pause Mode)		Provided
Rotation	Image	Provided
	Camera	Provided (0°/90°/180°/270°)
INPUT/OUTPUT		
Video Output		Composite (x1)
RGB Output		Provided (x1)
Audio Output		Provided (x1)
RGB Input		Provided (x2)
Audio Input		Provided (x2)
USB 2.0 Port		Provided (x1)
LIGHTING		
	Upper Lighting Unit	Provided (Twin LED lamp)
	Base Light	Backlight (210 x 297 mm)
OTHERS		
Supplied Accessories		User manual, Remote Control, AC Adapter, Power Cord, Video RCA Cable, Lens Cap, RGB Cable, USB Cable, Utility Software
Optional Accessories		Annotation Tools with Software (Interactive Pad/Panel)
Dimensions	Setup	336 X 435 X 510 mm
	Folded	330 X 360 X 90 mm
Weight		2.5 Kg
Application Software		Provided
Power Source	AC	100-240V, 50/60 Hz
Operating Temperature		0 - 40° C

**Due to continuous product development, the specifications may change without prior notice.*

***Product image(s) are for illustrative purposes only and may differ from the actual product.*

For Sales

Contact: +91 8588839434 Email: sales@globusinfocom.com



Globus Infocom Ltd.

C -1/2, Safdarjung Development Area, New Delhi - 110016

E-mail: info@globusinfocom.com, Website: www.globusinfocom.com

Toll Free: 1800-200-4398



Available on
GeM
Government e Marketplace

