

Information Kiosk

Access information at your **finger touch**
with Globus Smart Devices

Globus Information Kiosk provides an attractive and engaging platform with a 19" Touch Screen LCD to spotlight your self-service application. While the visual focus is on sophisticated presentation, the design houses a full array of Information components with highly interactive features.

Available as a smart standalone equipment, Globus Information Kiosk offers versatile enclosure options for virtually all common interactive & information devices. Integration of technology allows kiosks to perform a wide range of functions, evolving into self-service devices.



GK 19P

These "Self-Service Devices", are seen everywhere, whether it is in School/University Campus, Office Reception, Conference Room/Board Room, Auditorium, Postal Center or self-check-in at Airport, Railway Station & wherever access to information is desirable.

Globus Information Kiosk allows its users to access product and service information conveniently. The aesthetic and functional design of Globus Information Kiosk is a key element that drives user adoption and affordability.

* IP-65 compliance USB Metallic keyboard with track ball

Key features

- **Inbuilt PC**
- **Touch Monitor For Ease Of Use**
- **CRCA Steel Sheet Body For Long Life**
- **Pre-Loaded Microsoft Windows**



Globus Information Kiosk Specifications

Features	GK-19P
Type/Mounting	Free Standing, floor mounted with base and screw less chassis
Construction	1.6 mm thick CRCA steel sheet, with polymer powder coating
Safety	Vandal resistant design
Dimension (l x w x h)	668mm X 415mm X 1425mm
Display Type	
Type	48.3 cm (19") Colour LCD Touch Monitor
Resolution	SXGA (1280 x 1024)
Touch Screen	SAW type antiglare overlay vandal resistant tempered glass (3 mm thick)
Brightness	250 cd/m ²
Processing System	
Processor	Intel Processor, 2.13 GHz, 3 MB Cache
Chipset	Intel Chipset
Operating System	Windows 7 Professional
Memory	2 GB
Optical Drive	DVD (RW)
Hard Disk	320 GB
Network / Expansion I/O	1x PS-2, 4 x USB, 1 x Serial, 1 x LAN 10/100/1000, 1 x VGA
Audio	1 x Line-out/1 Line-in
Speaker	2 x 1.5 Watt RMS Stereo speaker
Softwares	Norton Anti Virus/Mcafee or equivalent with 1 year license
Power Supply	180 - 240V, 50Hz, AC Supply
CPU Operating Temp.	-10 °C ~ 55 °C
Environment	
Ambient temperature	5 Deg.C to 40 Deg.C
Storage Temperature	(-)10 Deg.C to 55 Deg.C
Operating Humidity	40 deg at 90% RH non-condensing
Storage Humidity	40 deg at 90% RH non-condensing
Cooling Fans	Two Fans for cooling
Power Consumption	Maximum 120 Watts
Safety	FCC Class B for EMC (for CPU and Display)

* Due to continuous product development, the specifications may change without prior notice.



Globus Infocom Ltd.
 A-22, Sector-4, Noida-201301
 District Gautam Budh Nagar (Uttar Pradesh) INDIA
 Tel: +91-120-4051700, 4051800, Fax: +91-120-4051726 / 827
 Email: sales@globusinfocom.com, Website: www.globusinfocom.com

Toll Free
1800-200-4398