

INNOVATIVE & INTEGRATED

Interactive Touch Screens

- Meeting infinity™ software embedded
- Intelligent Temperature control
- Word/PPT/PDF/Excel Viewer
- Input Resource Preview
- On Screen Annotation
- Supports Wi-Fi / LAN Printer
- Auto light adjustment
- Wi-Fi Hotspot functionality
- Display videos & pictures from smart phone / pad wirelessly (Optional)



Available Sizes - 55 inch, 70 inch Display

- Multi-Touch
- High Definition Display
- 24 x 7 Operation
- Easy Accessible ports in front
- Inbuilt OPS Processor (Optional)
- Plug & Play without any installation
- Integrated Wireless Interactive Presentation Solution (Optional)
- Deo System (Inbuilt Android, supports OPS for Windows)

Specifications - Interactive Touch Screens

Model Name	TWB-E55	TWB-E70
Backlight	LED (Backlit)	
Display Area	930.24 x 523.26 mm	1538.88 x 865.62 mm
Active Screen Size (Diagonal)	55"	70"
Aspect Ratio	16:9	
Resolution	1920 x 1080 Pixel	
Display Colors	1.06B	
Brightness	250 cd/m ²	
Contrast	5000:1	
Response Time	8 ms	
Video System / Audio System	PAL / NTSC / SECAM	
AV Inputs / Outputs	Inputs: USB Media Play Port x 1, Touch Frame USB Port x 3, HDMI x 2, S-Video x 1, YPbPr/YCbCr/Audio x 1, VGA x 3, PC Audio x 3, AV x 2, RS232 x 1 Outputs: AV x 1, SPDIF x 1, VGA x 1	
Speaker Output Power	15W x 2 RMS	
Multimedia File Formats Support	Video: MPEG1, MPEG2, MPEG4, H264, RM, RMVB, MOV, MPEG, VC1, Divx, FLV(Support 1080P HD Decoding) Audio: WMA, Mp3, M4A, (AAC)	
Power Consumption	Maximum < 180W Standby Mode < 0.5W	Maximum < 250W Standby Mode < 0.5W
Working Voltage	AC 100-240V, 50/60 Hz	
Wireless Interactive Presentation Solution (Optional)	Can connect to external gadgets (Microsoft / Android / iOS) wirelessly (draws power internally, without any external power source)	
Wireless Interactive Input Device		
Technology	Electromagnetic Interactive Device connected through RF	
Display	LCD Display for battery status, charging status etc.	
Input	Rechargeable EM Pen (charger housed within the panel body)	
Range	15 mtrs.	
Touch		
Touch Surface	5mm Tempered Glass (Anti Glare)	
Touch Sensor	IR	
HID Support	√	
Touch Points	Multi touch (10 points)	
Writing Tools	Pen or Finger	
Touch Resolution	32767*32767	
Scan Speed	5-9 ms	
Cursor Speed	125 Points/s	
Positioning Accuracy	1 mm	
Communication Interface	USB	
Storage Conditions / Packing Information		
Working Temperature	5° C ~ 40° C / 95% RH at 10%-80% Humidity	
Mounting (Optional)	Wall-mounted / Stand	
Outline Dimension	1301.98 x 771.92 x 97.4mm	1642.86 x 969.80 x 110.9mm
Packing Dimension	1440 x 900 x 265mm	1780 x 1100 x 282mm
Net Weight	46 KG	70 KG
Gross Weight	59 KG	83 KG
Standard Accessories	Power Cable, Wall Mount kit, Stylus pen (set of 4), User Manual, Remote control, Cables and connectors	

**Due to continuous product development, the specifications may change without prior notice.*

***Product image(s) are for illustrative purposes only and may differ from the actual product.*

For Sales

Contact: +91 8588839434 **Email:** sales@globusinfocom.com



A-22, Sector-4, NOIDA - 201301
 District Gautam Budh Nagar (Uttar Pradesh) INDIA
 Tel: +91-120-4051700, 4051800, Fax: +91-120-4051726
 E-Mail: info@globusinfocom.com
 Website: www.globusinfocom.com

TOLL FREE
1800-200-4398