

INTRODUCING

ULTRA SHORT THROW PROJECTORS

Key Features

- Auto Detection of Input Source
- Auto Power-Off on Signal Sourcing Failure
- High-speed Power off
- Image Freezing, Zoom (In/Out) & Panning
- One-Key Blank Screen
- Lamp & Filter countdown
- Anti-Theft Bar & lock



GLOBUS
ULTRA UST X30P

Globus Ultra UST X30P

Specifications

Model	Ultra UST X30P
Native Resolution	1024 x 768 (XGA)
Brightness	3000 Lumens
Contrast Ratio	2000 : 1
Lamp	215W NSH
Video Compatibility	NTSC 4.43, PAL-M, PAL-N, SECAM, DTV, HDTV(480i, 480p, 575i, 575p, 720p, 1035i & 1080i)
Input Compatibility	VGA, SVGA, XGA, SXGA, WXGA, UXGA, Mac
Projection Size	50" ~ 105"
Throw Ratio	0.45M ~ 0.99M
Keystone Correction	± 30°
Speaker	10W Mono
Input	VGA, Video, Audio 3.5 Mini Jack, RCA
Output	VGA, Audio Out
Control Port	RS232 / RJ45
Lamp Life	6000 Hrs. (Eco mode) & 4000 Hrs. (Normal Mode)
Power Consumption	Max. 300W
Lamp Hour Counter	Built-in
Remote	Full Functional Remote Control
Power Supply	100 - 240V AC, 50Hz
Operating Temperature	0° C to 50° C, 90% RH
Aspect Ratio	4:3 / 16:9
Special Features	Keystone Correction Auto Source Selection Top Loading Lamp Replacement Image Freeze, Zoom and Panning

**Due to continuous product development, the specifications may change without prior notice.*

***Product image(s) are for illustrative purposes only and may differ from the actual product.*

For Sales Contact: +91 8588839434 **Email:** sales@globusinfocom.com

