



Multimedia Projector

Perform with excellence with our new Ultra Series Projectors



Ultra X50U

★ Advanced Feature



XGA Resolution



Upto 2,500 Hours Long Lamp Life



5000:1 Contrast Ratio



Instant Restart + HDMI



±30 Degrees Keystone Correction

Specifications

Globus Ultra X50U

Technology	DLP
Resolution	XGA (1024 x 768)
ANSI Lumen	5000
Contrast Ratio	5000:1
Aspect Ratio	4:3 (5 aspect ratio selectable)
Throw Ratio	1.41 ~ 2.25
Display Color	1.07 Billion Colors
Zoom Ratio	1.6x
Lens	F=2.45~3.07, f=15.78~25.12
Lens Shift	Vertical: +7.5%
Keystone Correction	± 30 degrees
Computer Compatibility	VGA to UXGA
Video Compatibility	PAL, SECAM, NTSC
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
On Screen Display	Available (28 Languages)
Projection Lamp	Wattage: 370W, Part # X50370W
Lamp Life	Normal: 2000 hrs, Eco: 2500 hrs
Projection Size	60" ~ 240"
Projection Offset	107.5% ±2.5%
Horizontal Frequency	15KHz~102KHz
Vertical Scan Rate	24Hz~120Hz
Audio System	10 Watt x 2 with Built-In Speaker
Audible Noise	36/ 33 dBA (Normal/ Economic mode)
Terminal Ports	Computer IN x 1, Monitor Out x 1, S-Video In x 1, RCA IN x 1, HDMI x 2, Mini Jack Audio In x 1, Audio In x 1, Mini Jack Audio Out x 1, Rj45 x 1, USB (Type A) x 1, Rs232 x 1, IR Receiver x 1
Power Consumption	< 490 W (Typical), <0.5W (Standby)
Power Supply	AC 100V - 240V, 50-60 Hz
Weight	4.9 Kg.
Standard Accessories	Carry Bag, Full Function Remote Control with battery, power cable (1.5m), VGA cable (1.5m), User Manual CD, Professional Laser Pointer

**Due to continuous product development, the specifications may change without prior notice.*

***Product image(s) are for illustrative purposes only and may differ from the actual product.*

For Sales

Contact: +91 8588839434 **Email:** sales@globusinfocom.com



Globus Infocom Ltd.

A-22, Sector-4, NOIDA - 201301

District Gautam Budh Nagar (Uttar Pradesh) INDIA

Tel: +91-120-4051700, 4051800, Fax: 0120 - 4051827 / 726

E-mail: info@globusinfocom.com, Website: www.globusinfocom.com



TOLL FREE
1800-200-4398