

Experience the easiest way to Collaborate



Globus brings Hitevision Interactive Touch Panel (X7). With two wide angle cameras and full HD (1080 pixel) resolution you can see people as if they are present in your room, no matter wherever they are.

X7 Interactive Panel allows you to Share not only video and voice, but also data and annotations from the meeting. Get a sound that is always robust and clear with noise reduction and echo cancellation.

It has a sleek and impressive look that combines camera, microphone, speakers and other advanced technology with elegance. All in one design gives a benefit of quick and easy one time installation and next time onwards simply turn on X7 and start video conference.

Silent Features

- Intelligent light detector & thermo protector
- Input Resource Preview
- On screen annotation
- Works with any collaboration software
- Front I/O ports for easy access
- Discussion board
- Inbuilt Computer
- Android OS

Specifications

X7

Active Screen Size	70"
Display Area	1539 x 866mm
Display Ratio	16:9
Display Colors	10bit
Resolution	Full HD (1920 x 1080 Pixel)
Brightness	350 cd/m ²
Contrast	4000:1
Response Time	6ms
I/O Ports	Input: HDMI x 1, VGA x 1, USB(Touch) x 2, USB x 2, Audio x 1 Output: 3.5mm Line out x 1, HDMI x 1
Other Ports	USB 2.0 x 2, RS232 x 1, RJ45 x 1, USB 3.0 x 1, SD Card Reader
Speaker	30W (front speakers)
Multimedia File Formats Support	Image: JPEG, BMP, PNG Video: MPMPEG1, MPEG2, MPEG4, H.264, H.265, RM, RMVB, MOV, MJPEG, VC1, Divx, FLV (Support 1080P, 4K HD Decoding) Audio: MP3, M4A, (AAC)

Touch

Touch Surface	Tempered Anti-glare glass
Touch Sensor	P-Capacitive Touch
HID support	HID
Touch Points	10 Points Touch
Writing Tools	Pen or Finger
Touch Resolution	63488 x 35840
Scan Speed	180Hz
Cursor Speed	125Points/s
Positioning Accuracy	0.8mm
Communication Interface	USB

Camera

Position	Top x 1, Bottom x 1 (use only one at a time)
Lens	86°
Frame Rate	30fps / 60 fps
Video Resolution	1920 x 1080 @ 30fps max
Sensors	2M pixels

Environment

Storage Temperature/Humidity	-20°C~60°C / 10% ~ 90%
Working Temperature/Humidity	0°C~ 50°C / 10% ~ 90%

Power

Power Consumption	Maximum <250W
Standby Mode	≤ 0.5W
Working Voltage	AC 100-240V, 50/60Hz

**Due to continuous product development, the specifications may change without prior notice.*

***Product image(s) are for illustrative purposes only and may differ from the actual product.*

For Sales

Contact: +91 8588839434 **Email:** sales@globusinfocom.com



Globus Infocom Ltd.

A-22, Sector-4, NOIDA - 201301

District Gautam Budh Nagar (Uttar Pradesh) INDIA

Tel: +91-120-4051700, 4051800, Fax: 0120 - 4051827 / 726

E-mail: info@globusinfocom.com, Website: www.globusinfocom.com



TOLL FREE
1800-200-4398