





- Duo System: Built-in Android system, supports Mini-PC for Windows
- Plug & Play: Compatible with Microsoft Human Interface Device Protocol. User can experience the touch function without driver installation
- Eco-Friendly: LED backlight in our interactive touch screen offers a thinner panel, lower power consumption, better heat dissipation, brighter display and better contrast level and produce less pollution on disposal
- Multi-Touch: based on advanced infrared sensor technology 10 point touch to enhance the productivity
- Easy Maintenance: Sophisticated mechanical design for easy maintenance







## **Educational Institutes**

Board Rooms - Meeting Rooms - Training Rooms

Conference Rooms - Ops Rooms etc.

## IFPD (Interactive Flat Panel Display)

## **Technical Specifications**

Model	IFPD 55A	
Backlight	LED (Backlit)	
Panel Technology	IPS	
Active Screen Size (Diagonal)	139.7 cm (55 inches)	
Display Colors	1.07B (10 bit)	
Bezel Width	60 mm	
Aspect Ratio	16:9	
Resolution	1920 x 1080 (Full HD)	
Orientation	Portrait and Landscape	
Brightness	450 cd/m <sup>2</sup>	
Contrast	10000:1	
Response Time	6 ms	
Video / Audio System	PAL / NTSC / SECAM	
AV Inputs / Outputs	USB port for Android x 2, VGA IN x 1, VGA Out x 1, HDMI x 3, USB B Type for Touch x 1, LAN Port for Android x 1, Earphone Jack, SDIF, RS-232, YPbPr, Video IN, Video Out, DP, DVI-D, RGB, Audio	
Speaker Output Power	20W x 2	
Media File Format Support	Video: MPEG1, MPEG2, MPEG4, H264, RM, RMVB, MOV, MPEG, VC1, Divx, FLV(Support 1080P HD Decoding) Audio: WMA, Mp3, M4A, (AAC)	
Power Consumption	Maximum < 147W; Standby Mode ≤ 0.5W	
Working Voltage	AC 100-240V, 50/60 Hz	
Duty Cycle	24 x 7	
Viewing Angle	178:178 (Horizontal / Vertical)	
Presentation Solution (Optional)	Can connect to external gadgets ( Microsoft / Android / iOS ) wirelessly (draws power internally, without any external power source)	
Annotation / Signage Software	/ Signage Software Annotation Features like draw, choose, pens, annotate, erase, color, shapes, sizes, text, edit, fonts, stamp, move, capture picture, video, save, rotate, undo, image gallery, print, floating keyboard, background etc.	

Touch		
Touch Surface	Anti Glare Toughened Glass (3.2T)	
Touch Type	P-Cap	
HID Support	Available	
Touch Points	Multi touch 6 Points writing, 10 points touch	
Writing Tools	Pen or Finger (6mm object size for touch)	
Touch Resolution	32767*32767	
Response Time	10 ms	
Cursor Speed	125 points /sec	
Positioning Accuracy	1 mm	
Communication Interface	USB	

Others		
Internal Memory	64 GB (8 GB System)	
Web OS	Web OS 3.0	
PIP/ PBP	2 (PIP/ PBP)	



Storage Conditions / Packing Information			
Working Temperature / Humidity	5° C ~ 40° C / 95% RH at 40°C		
Mounting	Wall-mounted / Stand (Optional)		
Outline Dimension	1302 x 772 x 98 mm (L x H X D)		
Packing Dimension	1460 x 920 x 260mm (L x H x D)		
Net Weight	35 Kg		
Standard Accessories	Power Cable, VGA Cable, USB Cable, Audio Cable, Writing Pen x 3, User Manual, Remote Control, Wall-mount bracket		



## Corporate Office:

A-66, Sector-4, Noida, District Gautam Buddha Nagar, U.P., India - 201301 📞 0120-4051700/800 🖾 0120-4051827 🖶 info@globusinfocom.com

<sup>\*</sup>Due to continuous product development, the specifications may change without prior notice.

\*\*Product image(s) are for illustrative purposes only and may differ from the actual product.