



Enterprise Series

Globus Digital Display

MODEL: GM 65

GM 65

Application Areas



Educational Institutes

Board Rooms - Meeting Rooms - Training Rooms

Conference Rooms - Ops Rooms etc.

Globus Digital Display

Technical Specifications



Model	GM 65
Backlight	LED (Backlit)
Panel Technology	IPS
Active Screen Size (Diagonal)	139 cm (55 inches)
Display Colors	16.7M colors
Bezel Width	60 mm
Aspect Ratio	16:9
Resolution	1920 x 1080 (Full HD)
Brightness	500 cd/m ²
Contrast	4000:1 (Static Contrast); 300000:1 (Dynamic Contrast)
Response Time	8 ms
Video / Audio System	PAL / NTSC / SECAM
AV Inputs / Outputs	HDMI x 2, VGA (PC) x 1, Audio 3.5 mm In x 1, Mini AV Out, Headphone, USB x 2, AV Port x2
Speaker Output Power	20W x 2
Media File Format Support	Video: MPEG1, MPEG2, MPEG4, H264, RM, RMVB, MOV, MPEG, VC1, Divx, FLV(Support 1080P HD Decoding) Audio: WMA, Mp3, M4A, (AAC)
Power Consumption	200W; Standby Mode ≤ 0.5W
Working Voltage	AC 100-240V, 50/60 Hz
Duty Cycle	24 x 7
Viewing Angle	178:178 (Horizontal / Vertical)

Storage Conditions / Packing Information	
Working Temperature / Humidity	5° C ~ 40° C / 95% RH at 40°C
Mounting	Wall-mounted / Stand (Optional)
Standard Accessories	Power Cable, VGA Cable, USB Cable, Audio Cable, User Manual, Remote Control, Wall-mount bracket

Special Features	<ul style="list-style-type: none"> - USB Plug & Play - Play Movies and Music - Auto Sleep Timer - View Text files and Photos
------------------	--

*Due to continuous product development, the specifications may change without prior notice.
 **Product image(s) are for illustrative purposes only and may differ from the actual product.



Corporate Office:

A-66, Sector-4, Noida, District Gautam Buddha Nagar, U.P., India - 201301

☎ 0120-4051700/800 ☎ 0120-4051827 ✉ info@globusinfocom.com

📞 For Sales: 0 85888 39434 🌐 www.globusinfocom.com