



Enterprise Series

Digital Podium / Electronic Lectern

MODEL: GEL 203U

GEL 203U

Application Areas



Schools - Colleges - Universities

Board Rooms - Auditoriums - Conference Rooms

Ops Rooms - Training Rooms etc.

Digital Podium/ Electronic Lectern

Model: GEL 203U

Technical Specifications

Type/ Mounting	Free Standing, Wheel Mounted
Construction	Steel sheet, polymer powder coated, Wooden Top, all directional wheels with lock. No ports/wire exposed while the Podium is locked and not in use to avoid any kind of breakage or mishandling, Cooling Fans in lower body
Display	
Monitor	Highly sensitive, built-In Interactive Touch Monitor with manual tilt facility and mechanism to make the panel stable to avoid any kind of shake while wiring.
Screen Type	Color LED
Size	21.5" (54.61 cm)
Brightness	350 nits
Resolution	1920 x 1080 (Full HD)
Reading Accuracy	± 0.5mm (center)
Interactive Resolution	4000 Lpi
Computer Interface	USB, VGA/HDMI/DVI
Display Port	VGA and HDMI
Aspect Ratio	16:9/ 16:10
Response Time	5 ms
Viewing Angles	170(H) ; 160(V)
Touch	Finger and Stylus
Tracking Speed	200 points / sec.
Speakers	Inbuilt in display panel
Pen Pressure Sensitivity	2048 Levels
Annotation Software	Annotation Features like draw, choose, pens, annotate, erase, color, shapes, sizes, text, edit, fonts, stamp, move, capture picture, video, save, rotate, undo, image gallery, print, floating keyboard, background etc. Network classroom feature to conduct remote teaching by having interaction through all the three types of media Audio, Video and Text.
Console Panel Ports (Accessible from outer body of podium)	VGA In (other than input of PC to facilitate extra PC/ Laptop), USB port (to facilitate inputs directly from pen drives/USB etc.), RJ45 LAN Port
Central Controller with panel and video scalar	VGA In x 2, Audio In x 2, Video In x 2
Audio System	
Wireless Microphone System	Hand held Microphone x 1, Collar Microphone x 1, Wireless Microphone Receiver x 1 (10 meter range)
Gooseneck Microphone	21.5cm Phantom powered (no requirement of batteries thereby eliminating consumable cost) Gooseneck Microphone with XLR output, ON/OFF switch and LED light indicating ON/OFF status, permanently polarized condenser, highly directional featuring hyper cardioid /labar directivity
Amplifier and Speakers	50W RMS Amplifier and two speakers of 30W RMS each
System Details	
CPU Housing	Small form factor, 2L volume
Processor	Intel Core i3, 3.0 GHz (8th generation) Processor
Memory	8 GB
HDD/ Storage	1 TB
Audio	Line-Out x 1/ Line-In x 1
Wi-Fi	Built in Wi-Fi
I/O Expansion	USB 2.0 x 2, LAN 10/100/ VGA
Operating System	Windows 10 (Preloaded)
Antivirus	McAfee/ Norton antivirus with 1 year license
Power	
Power Supply	100 - 240V, 50Hz, AC
Power Consumption	120 Watt (Max)

*Due to continuous product development, the specifications may change without prior notice.

**Product image(s) are for illustrative purposes only and may differ from the actual product.



Corporate Office:

A-66, Sector-4, Noida, District Gautam Buddha Nagar, U.P., India - 201301

☎ 0120-4051700/800 📠 0120-4051827 ✉ info@globusinfocom.com

📞 For Sales: 0 85888 39434 🌐 www.globusinfocom.com