



Available on
GeM
Government
e Marketplace



Enterprise Series

Interactive Digital Board

MODEL: TWB UB65

Key Features

- Duo System: Built-in Android system, supports Mini-PC for Windows
- Plug & Play: Compatible with Microsoft Human Interface Device Protocol. User can experience the touch function without driver installation
- Eco-Friendly: LED backlight in our interactive touch screen offers a thinner panel, lower power consumption, better heat dissipation, brighter display and better contrast level and produce less pollution on disposal
- Multi-Touch: based on advanced infrared sensor technology 10 point touch to enhance the productivity
- Easy Maintenance: Sophisticated mechanical design for easy maintenance

Application Areas

Educational Institutes

Board Rooms - Meeting Rooms - Training Rooms

Conference Rooms - Ops Rooms etc.



Available on
GeM
Government e Marketplace

Interactive Digital Board

Technical Specifications



| | |
|-------------------------------|--|
| Model | TWB UB65 |
| Backlight | LED (Backlit) |
| Panel Technology | In Plane Switching (IPS) |
| Active Screen Size (Diagonal) | 164 cm (65 inches) |
| Display Colors | 1.07B (10 bit) |
| Bezel Width | 23 mm |
| Aspect Ratio | 16:9 |
| Resolution | 3840 x 2160 (UHD) |
| Orientation | Portrait and Landscape |
| Brightness | 450 cd/m ² |
| Contrast | 5000:1 |
| Response Time | 8 ms |
| Video / Audio System | PAL / NTSC / SECAM |
| AV Inputs / Outputs | HDMI, VGA, USB Port, RS232C, RJ45 |
| Speaker Output Power | 20W x 2 |
| Media File Format Support | Video: MPEG1, MPEG2, MPEG4, H264, RM, RMVB, MOV, MPEG, VC1, Divx, FLV(Support 1080P HD Decoding) Audio: WMA, Mp3, M4A, (AAC) |
| Power Consumption | Maximum < 185W; Standby Mode ≤ 0.5W |
| Working Voltage | 230 V AC, 50 Hz |
| Duty Cycle | 16 x 7 |
| Viewing Angle | 178:178 (Horizontal / Vertical) |

| | |
|-------------------------|---|
| Touch | |
| Touch Surface | Anti Glare Toughened Glass |
| Touch Sensor | IR |
| HID Support | Available |
| Touch Points | Multi touch 6 Points writing, 10 points touch |
| Writing Tools | Pen or Finger |
| Touch Resolution | 32767 x 32767 |
| Response Time | 10 ms |
| Cursor Speed | 125 points /sec |
| Positioning Accuracy | 1 mm |
| Communication Interface | USB |

| | |
|--|---|
| Storage Conditions / Packing Information | |
| Working Temperature / Humidity | 0° C ~ 45° C / 85% RH |
| Dimension | 155 x 93 cm |
| Weight | 53 Kg |
| Mounting | Wall-mounted / Stand (Optional) |
| Standard Accessories | Power Cable, VGA Cable, User Manual, Remote Control, Wall-mount bracket |

*Due to continuous product development, the specifications may change without prior notice.
**Product image(s) are for illustrative purposes only and may differ from the actual product.



Corporate Office:

A-66, Sector-4, Noida, District Gautam Buddha Nagar, U.P., India - 201301

☎ 0120-4051700/800 📠 0120-4051827 ✉ info@globusinfocom.com

📞 For Sales: 0 85888 39434 🌐 www.globusinfocom.com