



Enterprise Series

Vertical Signage Display

MODEL: GIL-55 VS-1

GIL-55 VS-1

Application Areas



Educational Institutes

Board Rooms - Meeting Rooms - Training Rooms

Conference Rooms - Ops Rooms etc.

Vertical Signage Display

Model: GIL-55 VS-1

Technical Specifications

Type/Mounting	Floor standing
Construction	Ultra thin, clean cut, durable and air cooled design, long lasting anti corrosive protection layer with structure of Galvanized steel

Display	
Type	55" Color, direct LED backlight source, laminated tempered glass
Resolution	Full HD (1920 x 1080)
Active Area	1210 x 680
Screen Orientation	Vertical / Horizontal
Brightness	500 cd/m ²
Contrast Ratio	4000:1
Viewing Angle	178° / 178° (H/V)
Aspect Ratio	16:9
Refresh Rate	6.5 ms
Inbuilt Speaker	10W x 2

System	
Processor	Intel Core i3, 3.1 Ghz
Memory	4 GB
Storage	1 TB HDD
Operating System	Windows 10 SL

Ports	
Video Input	USB x 1, SD x 1, HDMI x 1

Function	
File Format Support	Video: avi, mpg, dat, rm / rmbv, wmv; Audio: mp3, wma, m4a /aac; Image: .jpg / jpeg, bmp, png

Environment	
Power Consumption	380V (Standby: 2W; Power Shut off: 0.5W)
Power Supply	AC 100-240 50/60 Hz

Special Features	
<ul style="list-style-type: none">- Built-In voltage protection circuit- Automatic brightness adjustment according to surrounding- Automated on/off timing by day, week and hour	



*Due to continuous product development, the specifications may change without prior notice.
**Product image(s) are for illustrative purposes only and may differ from the actual product.



Corporate Office:

A-66, Sector-4, Noida, District Gautam Buddha Nagar, U.P., India - 201301

☎ 0120-4051700/800 ☎ 0120-4051827 ✉ info@globusinfocom.com

📠 For Sales: 0 85888 39434 🌐 www.globusinfocom.com