



Available on
GeM
Government
e Marketplace



VISUALIZER - Enterprise Series

Globus introduces latest range of eco-friendly visualizers

MODEL: GVP - 502

GVP-502

Application Areas

Schools - Colleges - Universities

Corporate Offices - Meeting Rooms - Training Rooms

Huddle Rooms - Conference Rooms



Available on
GeM
Government
e Marketplace

Visualizer

Technical Specifications

Model GVP - 502

| Camera | | |
|----------------------|----------------|---|
| Image Pick-up Device | | CMOS Technology |
| Total Pixels | | 5 Mega pixels |
| Effective Pixels | | 1920 x 1080 |
| Frame Rate | | 30 FPS |
| Resolution | RGB Output | HD (1920 x 1080) |
| | Aspect Ratio | 16:9 |
| | Video Output | 950 TV lines |
| | Signal Support | 1024 x 768; 1280 x 1024; upto 1920x1080 |

| Optics | | |
|---------------|--|----------------------------|
| Optical Zoom | | 12x |
| Digital Zoom | | 8x |
| Lens | | F1.6 ~ 3.7, f 3.9 ~ 46.8mm |
| Shooting Area | | 380 mm x 285 mm |
| Focus | | Auto / Manual |

| Functions | | |
|---------------------------|--------|------------------------|
| Graphics Interface | | Provided |
| Computer Interface | | USB with software |
| Split Screen | | Provided |
| White Balance | | Auto / Manual |
| Brightness Control | | Provided |
| SD Card Slot | | Provided |
| Image Memory | | 500 Images |
| Mirror Image | | Provided |
| Color / B&W Selection | | Provided |
| Freeze (Pause Mode) | | Provided |
| Preview | | Provided |
| Electronic Volume Control | | Provided |
| Rotation | Image | 0° / 90° / 180° / 270° |
| | Camera | Provided (350° H/V) |

| Input / Output | | |
|---------------------------|--|----------|
| HDMI Input | | Provided |
| VGA Input | | Provided |
| Audio Input | | Provided |
| USB 2.0 Port | | Provided |
| Mic Input | | Provided |
| HDMI Output | | Provided |
| VGA Output | | Provided |
| Audio Output | | Provided |
| Direct Mouse Connectivity | | Provided |

| Lighting | | |
|----------|---------------------|--------------------------|
| | Upper lighting unit | Provided (Twin LED lamp) |
| | Base light | Backlight (210 x 297 mm) |



| Others | | |
|-----------------------|----|--|
| Supplied Accessories | | User manual, Remote control, AC adapter, Power cord, Video RCA cable, Lens cap, RGB Cable, USB cable, Utility software |
| Optional Accessories | | Annotation tools with software (Interactive Pad/ Panel) |
| Dimensions | | 336 x 435 x 510 mm (W x D x H) |
| Weight | | 2.8 kg |
| Application Software | | Provided |
| Power Source | AC | 100-240V, 50/60 Hz |
| Operating Temperature | | 0°-50°C |

*Due to continuous product development, the specifications may change without prior notice.

**Product image(s) are for illustrative purposes only and may differ from the actual product.



Corporate Office:

A-66, Sector-4, Noida, District Gautam Buddha Nagar, U.P., India - 201301

☎ 0120-4051700/800 ✉ 0120-4051827 📧 info@globusinfocom.com

📞 For Sales: 0 85888 39434 🌐 www.globusinfocom.com