



VISUALIZER - Enterprise Series

Globus introduces latest range of eco-friendly visualizers

MODEL: GVP - 441

GVP-441



Application Areas

Schools - Colleges - Universities

Corporate Offices - Meeting Rooms - Training Rooms

Huddle Rooms - Conference Rooms

Visualizer

Technical Specifications

Model GVP - 441

| Camera | | |
|----------------------|------------|---|
| Image Pick-up Device | | CMOS Technology (0.33 inch) |
| Total Pixels | | 5M pixels |
| Effective Pixels | | 1920 x 1080 |
| Signal Support | | 1024 x 768, 1280 x 1024, upto 1920 x 1080 |
| Frame Rate | | 30 FPS |
| Resolution | RGB Output | Full HD (1920 x 1080) |
| Layout | | Landscape |

| Optics | | |
|---------------|--|----------------------|
| Optical Zoom | | 12x |
| Digital Zoom | | 15x |
| Shooting Area | | A4 (210 mm x 290 mm) |
| Focus | | Auto / Manual |

| Functions | | |
|--------------------------------|-------|------------------------|
| Graphics Interface | | Provided |
| Computer Interface | | USB with software |
| Brightness Control | | Provided |
| White Balance | | Auto / Manual |
| PIP/ PBP | | Provided |
| Preview | | Provided |
| Negative / Positive Conversion | | Provided |
| SD Card Slot | | Provided |
| Image Memory | | 128 Images |
| Mirror Image | | Provided |
| Color / B&W Selection | | Provided |
| Freeze (Pause Mode) | | Provided |
| Direct Mouse Connectivity | | Provided |
| Rotation | Image | 0° / 90° / 180° / 270° |

| Input / Output | | |
|----------------|--|----------------|
| HD Output | | HDMI |
| Video Output | | Composite (x1) |
| RGB Output | | Provided (x1) |
| Audio Output | | Provided (x1) |
| RGB Input | | Provided (x2) |
| Audio Input | | Provided (x2) |
| USB 2.0 Port | | Provided (x1) |
| RS232 | | Provided (x1) |
| HD Input | | HDMI |

| Lighting | | |
|----------|---------------------|--------------------------|
| | Upper lighting unit | Provided (Twin LED lamp) |
| | Base light | Backlight (210 x 297 mm) |

| Others | | |
|-----------------------|----|--|
| Supplied Accessories | | User manual, Remote control, AC adapter, Power cord, Video RCA cable, Lens cap, RGB Cable, USB cable, Utility software |
| Optional Accessories | | Annotation tools with software (Interactive Pad/ Panel) |
| Dimensions | | 336 x 435 x 510 mm (W x D x H) |
| Weight | | 2.8 kg |
| Application Software | | Provided |
| Power Source | AC | 210-230V, 50/60 Hz |
| Operating Temperature | | 0°-40°C, 85% RH |



*Due to continuous product development, the specifications may change without prior notice.

**Product image(s) are for illustrative purposes only and may differ from the actual product.



Corporate Office:

A-66, Sector-4, Noida, District Gautam Buddha Nagar, U.P., India - 201301

☎ 0120-4051700/800 📠 0120-4051827 ✉ info@globusinfocom.com

📞 For Sales: 0 85888 39434 🌐 www.globusinfocom.com