



## VISUALIZER - Enterprise Series

Globus introduces latest range of eco-friendly visualizers

MODEL: GVP - 702

### Advanced Features

- Vivid & Convincing Presentation Tool
- Built in LED on Camera Head
- Dazzling, incredible Crystal Clear Picture
- Empowers Quality Learning Experience
- Kensington anti-theft lock device
- Power to Engage & Communicate Effectively
- High speed image transmission
- Displays Books, Photos & 3D Objects
- High color reproduction

# APPLICATION AREAS

Schools - Colleges - Universities

Corporate Offices - Meeting Rooms - Training Rooms

Huddle Rooms - Conference Rooms

## Visualizer

### Technical Specification

**Model** GVP - 702

Camera		
Image Pick-up Device		1/3" CMOS sensor
Sensor		5M pixels
Frame Rate		30 FPS
Color reproduction		1600 x 1200; 1024 x 768
Resolution	Output	XGA, SXGA (1280 x 1024), WXGA, 1080p
	Aspect Ratio	5:4
	Video Output	700 (H) TV lines

Optics		
Zoom		2x pixels
Mechanical Zoom		9x pixels
Digital Zoom		12x pixels
Close Up		40 mm (1.6")
Shooting Area		> A3 (442 x 331 mm)
Focus		Auto / Manual
Sharpness		1023 Lines MTF
Signal to Noise Ratio		51dB

Functions		
Graphics Interface		Provided
Computer Interface		USB with software
Image Transmission		USB 2.0 (480 Mbps)
Split Screen		Provided
White Balance		Auto / Manual
Negative / Positive Conversion		Provided
Audio/Video Recording		Provided (One touch button to record image and sound synchronously)
Image Capture		Provided (Single or continuous capturing)
Auto Tune		Provided (One button for image optimization)
Freeze (Pause Mode)		Provided
Electronic Volume Control		Provided
Rotation	Image	0°, 180°, Flip, Mirror

Input / Output		
VGA		Provided (x1)
Audio Input		Provided (minijack x1)
C-Video		Provided (RCA x1)
Mic		Provided (Phone Jack x 1)
HDMI		Provided (x1)
Microphone		Provided (Built-in)
USB 2.0 Port		Provided (x2)

Lighting		
	Built-In LED	Provided (LED side lamp supported by Gooseneck camera head)

Others		
Supplied Accessories		User manual, Remote control, AC adapter, Power cord, Video RCA cable, Lens cap, RGB Cable, USB cable, Utility software
OS Support		Windows XP, Vista, 7, 8, 10, Mac OS X, Chrome OS, iOS and android app; WIA and TWAIN interface
Application Software		Provided
Power Source	AC	100-240V, 50/60 Hz
Operating Temperature		0°-50°C



\*Due to continuous product development, the specifications may change without prior notice.

\*\*Product image(s) are for illustrative purposes only and may differ from the actual product.

For Sales

Contact: 0 85888 39434

Email: sales@globusinfocom.com



**Globus Infocom Limited**

A-66, Sector-4, Noida - 201301 (U.P.)

Email: info@globusinfocom.com

Website: www.globusinfocom.com

Toll Free: 1800-4194-398

