

Application Areas



Educational Institutes



Board Rooms



Training Rooms



Conference Rooms

and many more..

Nationwide Sales & Service Presence



Corporate Office: A-65, Sector-4, Noida, District Gautam Budh Nagar,
Uttar Pradesh - 201301, India | **Phone:** +91-120-4051700, 4051800
Email: info@globusinfocom.com | **www.globusinfocom.com**



Video Conferencing Ultra HD PTZ Camera

ImpactVC202K

Perfect need-based camera catering to the conferencing requirements of huddle rooms, conference rooms, auditoriums, etc. of varied dimensions and sizes. It offers Ultra HD resolution also provide crystal clear image even under low light conditions.

Communication
made
Impactful





High Resolution and Optimum Zoom

Comes with a superior and crystal-clear video resolution of 2160 p which supports 4x of powerful optical zoom. It brings a vast range of clarity to your video conferencing while increasing the communication capability.

Design & Construction

Solid and rugged video conferencing which imparts a premium look to your experience. It can be mounted on the top panel/monitor for better space management.




High Quality Images in Low Light

The CMOS sensor accounts for exception performance and high quality images even in low light conditions due to its high signal-to noise ratio.

Auto White Balance and Brightness Control

Adjusts brightness and white balance automatically to optimize video quality. This feature helps the user attain a flawless video conferencing output.



Technical Specification

4K UHD PTZ Video Conferencing Camera

Model	ImpactVC202K
Optical Zoom	4x
Digital Zoom	2x
Camera Resolution	2160p (4K)
Sensor	1/2.5" CMOS Sensor
Effective Pixels	8 MP
Scanning Mode	Progressive
Aspect Ratio	16:9
Minimal Illumination	0.5 Lux @ (F1.8, AGC ON)
Shutter	1/30s ~ 1/10000s
Camera Panoramic View	Supported
White Balance	Auto, Indoor, Outdoor, One Push, Manual
Backlight Compensation	Support
Digital Noise Reduction	2D&3D Digital Noise Reduction
Video S/N	≥55dB
Field of View	82°
Horizontal Rotation Range	350°
Vertical Rotation Range	±30°
Anti-Flickering	Supported
Built in Microphone Array	Available with upto 6 Mtr. Audio Pickup
Number of Pre-set	255, 10 pre-sets on Remote control
Pre-set Accuracy	0.1°
Video System	HDMI: 4K@30fps, 1080P@60fps, 1080P@50fps, 1080I@60fps, 1080I@50fp, 1080P@30fps, 1080P@25fps, 720P@60fps 3G-SDI: 1080P@60fps, 1080P@50fps, 1080I@60fps, 1080I@50fp, 1080P@30fps, 1080P@25fps, 720P@60fps

Feature	
System Supported	Windows, Mac OS X/Linux/Android

Port Interface	
Connectivity	1x HDMI/USB

Generic Specification	
Input Voltage	DC 12V
Current Consumption	12V - 1.0A(MAX)
Operating Temperature	0°C ~ 40°C
Storage Temperature	-20°C ~ 60°C
Power Consumption	12W (Max)

*Due to continuous product development, the specifications may change without prior notice.
**Product image(s) are for illustrative purposes only and may differ from the actual product