





Impact Series Revolving Chair MODEL: Azure Midback-C

Model	Azure Mid Back
Seat	Made up of 1.5 \pm 0.1 cm thick hot - pressed plywood upholstered with fabric and moulded polyurethane foam, Polyurethane foam for seat is of density= $40 \pm 3 \text{kg/m}$
Construction	Upholstered with a fabric of 220 GSM \pm 5%(Gram::Square Meter). Mesh back and the backrest made up of two pieces injection moulded frame, height adjustable with height adjustment up to 90mm \pm 5(mm) and 2 way adjustable armrest
Seat	Made up of $12mm \pm 1(Mm)$ thick plywood, Synchronic tilt mechanism
Armrest	Armrest is made of injection moulded Polypropylene which is connecting seat and back
Mechanism Type	360° revolving type, Centre – Tilt, Tilt with upright lock, pneumatic height adjustment has a stroke of 10 ± 0.5 cm, pedestal is injection moulded Polyamide and fitted with 5 nos. twin wheel castors, twin wheel castors are injection moulded nylon base, pedestal is 66.1 ± 0.5 cm P.C.D.
Overall Size	Overall Width: 610mm (±10 Mm). Backrest Height 570 mm ±15 Mm. Backrest Width 520 mm ±10 Mm. Seat Height 440 mm ±10 Mm. Seat Width 520 mm ±10 Mm. Seat Depth 480 ±10 Mm. Thickness of MS Plate Joining The Under Structure With Seat:5 mm. Pedestal Size (Diameter In Mm) 650 mm ±10 Mm
Push Back	The Chair push back chair with upright position locking



Corporate Office:

A-66, Sector-4, Noida, District Gautam Buddha Nagar, U.P., India - 201301

^{*}Due to continuous product development, the specifications may change without prior notice.
**Product image(s) are for illustrative purposes only and may differ from the actual product.