



U Shaped Conference Table

Caroline-Conference Table

Ergonomic design and high-quality table

Specifications	
Construction	Assembling components include minifix dowels, pins, and MS brackets.
Table Top	The table features a 25mm thick pre-laminated particle board (Grade II as per IS 12823) with an approved laminate and finish in the specified shade. The worktop is sealed with a 2mm impermeable PVC strip, attached using edge banding machinery at 200°C. The table top is supported by a particle board base gable end, with floor-protective buffers to prevent floor scratches.
Modesty panel	The table is covered with an 18mm thick modesty panel, ensuring structural stability. The panel is made of pre-laminated particle board with proper PVC edge banding, connected at both ends
Wire carrier	A power connection opening, measuring 60mm x 125mm, is incorporated beneath the table top. It's constructed using 0.8mm thick high yield strength CRCA sheet (grade 'D') as per IS:513 standards, and is coated with powder for protection.

*Due to continuous product development, the specifications may change without prior notice.

**Product image(s) are for illustrative purposes only and may differ from the actual product.



Corporate Office:

A-66, Sector-4, Noida, District Gautam Buddha Nagar, U.P., India - 201301

☎ 0120-4051700/800 ☎ 0120-4051827 ✉ info@globusinfocom.com

☎ For Sales: 0 85888 39434 🌐 www.globusinfocom.com