



Impact Series  
Ceiling Tile Microphone  
Model No - Dazzle GODM-02



Ceiling Tile Microphone	Dazzle GODM-02
Pick-up pattern	Beam Pattern with 30 microphone capsule cover up to 600 Sq ft area
Max. SPL	104 dB SPL
Dynamic range	93 dB
Latency	<16 ms
Audio Output:	1 x 3-pin terminal, 1 x Digital Dante Network Audio (RJ-45 Primary and Secondary)
Ethernet / Control	1x PoE RJ 45
Supply voltage	44 – 57 V DC PoE
Transducer	Pre-polarized condenser microphone
frequency response	160 Hz - 18,000 Hz
Sensitivity	0 dBV/Pa (988 mV/Pa)
SNR	80 dB; Equivalent Noise level: 20(A)
Power consumption	8.8 W

\*Due to continuous product development, the specifications may change without prior notice.

\*\*Product image(s) are for illustrative purposes only and may differ from the actual product.



Corporate Office:

A-66, Sector-4, Noida, District Gautam Buddha Nagar, U.P., India - 201301

☎ 0120-4051700/800 ☎ 0120-4051827 ✉ info@globusinfocom.com

☎ For Sales: 0 85888 39434 🌐 www.globusinfocom.com