Nationwide Sales & Service Presence





Corporate Office: A-66, Sector-4, Noida, District Gautam Budhha Nagar, Uttar Pradesh - 201301, India | Phone: +91-120-4051700, 4051800 Email: info@globusinfocom.com | www.globusinfocom.com



Digital Projectors

Laser Projectors Dazzle-SWiV8


Globus Laser Projector is equipped with superior picture quality, long-life and reliability to amplify any lesson, meeting or seminar with vivid colours, bold graphics and razor-sharp clarity. Our laser projectors work on LP Technology for high-end and reliable performance.





Laser Phosphor Technology

New generation features in Laser Phosphor Technology like colour performance, lamp-free design and instant on/off facility, having advanced brightness and better heat resistant and its small module design makes the images more consistent and compact proving it to be more reliable in various scenarios.






High Brightness for Spectacular Visual Performance

High brightness of 6000 ANSI Lumens and High Contrast Ratio of 3000000:1 for razor-sharp and luminous picture quality in any given lighting condition be it too dark or too bright.

Perfectly Geometrical Images with H/V Keystone Correction

Vertical/Horizontal Keystone Correction of $H:\pm40^\circ$, $V:\pm40^\circ$ for obtaining perfect geometrical shape of the projection, eliminating trapezoid effect without moving the projector physically. The keystone can be adjusted via remote control.





Optical Zoom 1.3x

Globus Laser Projector comes with the Optical Zoom of 1.3x for greater flexibility in projection and high quality picture.

Technical Specification

Laser Projector	
Native Resolution	WUXGA (1920x1200)
Display Color	1.07 Billion Colors
Light Source	Laser Phosphor system
Brightness	6000 ANSI Lumens
Contrast Ratio	300000:1
Throw Type	Standard Throw (.91 to 2.5)
Throw Ratio	1.13-1.47
Optical Zoom	1.3x
Digital Zoom	0.8x - 2.0x
Lens	F=1.94-2.06, f=12-15.6mm
Throw Distance	0.73-9.50m,(100"@2.43m)
Image Size	30"-300"
Keystone & Corner Correction	Horizontal & Vertical (± 40°)
Audible Noise	35dB in Normal Mode, 28dB in Eco. Mode
Light Source Life	30000 Hrs in Normal Mode, 40000 Hours in Economy Mode
Input Ports	HDMI x 2, Computer in/VGA x 1, S-Video x 1, Composite video x 1, Audio In (3.5mm) x 1, Audio In (RCA R/L) x 1
Output Ports	VGA out x 1, Audio Out x 1
Other ports	USB type A (power) x 1, RJ45 x 1, RS232 x1, DC 12 V out
InBuilt Speaker	2 x 20 Watts rms to deliver full range sound
Input Resolution Support	VGA(640 x 480) to WUXGA(1920 x 1200)
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility	NTSC, PAL, SECAM
Power Consumption	Normal: 430W, Standby: <0.5W
Ingress Protection	Sealed Optical Engine with IP5X to prevents dust and moisture from entering the projector and affecting the thermal system
Input Power Supply	As per Indian standard with compatible power cable & connector
Accessories	All device driver and cables for connecting with computer
Remote	Full function remote control
Certificates	BIS