

Application Areas



Educational Institutes



Board Rooms



Training Rooms



Conference Rooms

and many more..



Digital Podium

Impact Series - DP 200C

A modern and well organised presentation & lecture device for seamless presentations that make two-way interaction between the presenter and audience even more efficacious.

Nationwide Sales & Service Presence



Corporate Office: A-66, Sector-4, Noida, District Gautam Budh Nagar,
Uttar Pradesh - 201301, India | **Phone:** +91-120-4051700, 4051800
Email: info@globusinfocom.com | **www.globusinfocom.com**





Interactive Panel

Comes with annotation software to make your session even more facile, interesting & enthralling as it allows to annotate on live screen. It performs functions like highlighting, saving, editing, mailing, printing and many more.



Multimedia Controller

To connect your devices like laptops and PCs, our Digital Podium also includes a Multimedia Controller which acts as a central point for all the input ports and control buttons. It houses ports including HDMI, USB 3.0 x 2, VGA Port, Audio In ports available on front panel.

Sliding Shutter

Interactive Panel in podium comes with a sliding shutter on top of it which is lockable. The purpose of providing lockable sliding shutter with panel is to keep it safe from unwanted breakage when not in use.

Inbuilt Ports & Cooling Fan

USB, VGA/DVI/HDMI ports are inbuilt in all our podiums to help you delivering a tussle free lecture. Digital Podium is also equipped with cooling fans that help to provide longer operation hours.

Technical Specifications

Digital Podium - DP 200C	
Wheel mounted capable of moving in all directions with a facility of lock them while the Electronic podium is in use, polymer powder coated steel body enclosure with wooden top panels, designed to work in suitable environmental conditions, wooden top having lock and key and a sliding cover for opening / closing easily, housing and connectivity for visual presenter while the visualiser is in use and not in use, at the time of using the visualiser, drawer can be opened and Visualiser can be used, no port exposed on the outer body for breakage, cooling fans provided in the lower body and Acrylic logo	

Sliding Trays	
To keeping laptop and Keyboard & Mouse	

Display	
Panel	Manual Tilt Facility
Monitor	Highly sensitive Interactive Touch Monitor and mechanism to make the panel stable to avoid shake while wiring
Screen Type	Color LED; Scratch resistant, antiglare & overlay tempered vandal resistant glass (3mm thickness)
Size	53.0 cm (21 inches)
Resolution	1920 x 1080 (Full HD)
Aspect Ratio	16:9/ 16:10
Response Time	5 ms
Computer Interface	USB x 1, VGA/HDMI/DIV x 1
Interactive Resolution	4000 Lpi (lines per inch)
Reading Accuracy	±0.5 mm (center)
Tracking Speed	200 points per second
Pen Pressure sensitivity	2048 Levels
Viewing Angles	170(H) ; 160(V)
Touch	Finger and Stylus
Speakers	Inbuilt in display panel

Mini PC	
Processor	Intel Core i5 10th Gen
Small Form Factor	2 litres
Wi-Fi /Wireless LAN Card	In-Built
RAM HDD	8 GB 500 GB SSD
Ports	HDMI x 1, DP (Display Port) x 2, USB ports x 5, LAN Port x 1
Keyboard & Mouse	Wireless
Operating System	Windows 10
Antivirus	Norton Anti-Virus/MacAfee with 1 year license

Multimedia Controller	
Built in HDMI Repeater	HDMI Output port support 15mtr HDMI cable
Ports on Rear Panel of Controller	USB 3.0 x 2, VGA Input x 2, VGA Output x 2, RCA Audio IN x 1, RCA Audio Output x 2, HDMI Input x 2, HDMI Output x 2 , Programming Port (Phoenix connector)
Buttons on front Panel of Controller	Push buttons to control volume up & down, volume mute to switch sources of HDMI visual presenter, VGA visual presenter, HDMI laptop, PC HDMI, VGA laptop, VGA PC & Controller Power On/Off, Display Power On and Power Off
Ports on front Panel of Controller	VGA, HDMI, USB3.0 x 2, Audio IN
Power Adaptor	5 V DC
Controller Resolution Output	4K (3840 x 2160)

Security	
Physical Key for secure access to system.	

Audio System and Microphones	
Gooseneck Microphone	Phantom powered gooseneck microphone with XLR output, 21.5cm length, ON/OFF switch and with LED ON/OFF light, permanently polarised condensor, highly directional featuring hypercardioid / lobar directivity.

Power	
Power Consumption	120 Watts
Power Supply	180-240V, 50Hz, AC Supply

*Due to continuous product development, the specifications may change without prior notice.
**Product image(s) are for illustrative purposes only and may differ from the actual product.