Nationwide Sales & Service Presence





Digital Podium

Model: DP 300B

A modern and well organised presentation & lecture device for seamless presentations that make two-way interaction between the presenter and audience even more efficacious.










Aesthetically-pleasing, premium design

Globus Interactive Podium is sleek, compact in form factor and premium in design, adding aesthetic value to the place it is installed. It is made up of ABS polycarbonate for a premium finish and robust design.

PCAP and Electromagnetic Touch Technology

Projected Capacitive (also PCAP) and Electromagnetic Touch Technology provide accurate and highly sensitive touch. It supports both pen as well as finger touch.





Microphones

The Gooseneck microphone comes with a dedicated On/Off button along with an LED indicator. It is powered by a Phantom Power Supply . This podium also comes with wireless microphones apart from gooseneck microphone, to make two way communication more impactful and convenient.

Single Lock for Both Slider and Cabinet



Our Smart Podium can be locked when not in use, using a single locking mechanism for both Slider and Cabinet.

Technical Specifications

Construction

Mild Steel material, sliding tray for Keyboard and mouse, flexible options in sizes for the 19"/ 21" and 22" Interactive Panel to fit in with positioning motorized up and down, top made with wood, space for the Desktop in the 21" rack for the equipment's to fit in, Sliding Shelf/Tray with Locks - For placement of extra lap top or Document and for Presenter with Internal Lock and door lock available.

| LED Interactive Panel | |
|------------------------|---|
| Construction | Positioning motorized up and down |
| Technology | Electromagnetic Touch Technology with Pen, Active Matrix color TFT |
| Size | 21 inches |
| Resolution | 1920 x 1080 |
| Display Colour | 16.7 million |
| Contrast Ratio | 800:1 |
| Aspect Ratio | 16:9 |
| Interface | USB |
| Inputs | НОМІ |
| Data Report | 125 Reports/Sec |
| Touch | Work independently for the both Laptop and PC whichever source is selected PC/Laptop when both are connected to the Podium the content appear on Interactive Panel along with touch activated of the selected source, automatically without detaching or attaching a cable. |
| Accuracy | ±0.5 mm |
| Max Reach Height | 8mm |
| Pressure sensitivity | 2048 Levels |
| Interactive Resolution | 4000 Lpi (lines per inch) |

| Programmable Multimedia Controller | | |
|---------------------------------------|---|--|
| Ports on front Panel of Controller | 17 Membrane Keys for Control, HDMI x 1, VGA x 1, 3.5mm Audio In x 1, LAN Port x 1, USB x 2, 6.35mm Mic In Port x 1, Power Plug of 220 Volt x 1 | |
| Ports on Rear Panel of Controller | HDMI In x 2, VGA Matrix x 2, USB x 1, USB Type C x 1, Video In x 2, Video Out x 2, Audio Left x 2, Audio Right x 2, Projector Power x 1, Electric screen power x 1, HDMI Out x 1, RS232 x 1, Projector IR Controller, | |
| Buttons on front Panel of Controller | Projector On Off, Motorised Screen Up & Down, Switching between PC, Visual Presenter and laptop, Volume Control | |
| Additional Ports (left Panel) | USB 2.0 x 2, Power Plug x 1, HDMl x 1, VGA x 1, LAN x 1, Mono x 1, Audio Video x 1 | |
| Connectivity Ports (Bottom) | LAN x 1, VGA x 1, HDMI x 2, Power Plug x 1, Gooseneck Mic Port x 1 | |
| Integrated Port (at top of following) | HDMI, VGA, USB x 2, LAN Port, 1 x Power Plug, 1 x Video Input, 1 Audio Input, Mic Input | |
| Power | 220 Volt AC | |

| Mini PC with Recording and Streaming Software | | |
|---|---------------------------------------|--|
| Processor | Intel Core i7 12th Gen | |
| Wi-Fi / Wireless LAN Card | In-Built | |
| RAM | 32 GB | |
| Hard Disk | 256 GB SSD with 1 TB HDD | |
| Ports | HDMI x 1, USB ports x 4, LAN Port x 1 | |
| Keyboard and Mouse | Wireless | |
| Operating System | Windows 10 Pro | |

| Audio System and Microphones | |
|---|---|
| System Audio (Amplifier, Speaker & Microphones) | 130 watt inbuilt amplifier & 2 speakers of 3 0 Watt each and one number of wireless Hand Held mic and One number of wireless collar mic |
| Gooseneck Microphone | Phantom powered gooseneck microphone with XLR output, 21.5cm length, ON/OFF switch and with LED ON/OFF light, permanently polarised condensor, highly directional featuring cardioid / lobar directivity. |

| Power Supply | |
|----------------------------|--|
| 180 -240V, 50Hz, AC Supply | |

^{*}Due to continuous product development, the specifications may change without prior notice.

**Product image(s) are for illustrative purposes only and may differ from the actual product.