





## Impact Series Motorised Dome Network Camera MODEL: G-SC-DI2N3T

Model	G-SC-DI2N3-T
Image Sensor	1/2.7 Progressive Scan CMOS
Effective pixels	2592x1944 Effective pixels
Camera Image sensing Capacity	5MP (Picture mode)
IR Distance	IR Distance 30 Mtr
Minimum Illumination	Color: 0.001Lux@F1.6, B/W: 0Lux with IR on
Shutter Speed	Auto/Manual, 1s ~ 1/100000s
Frame Per Second	20fps@2592 1944, 25fps@2592x1520,1920x1080, 1280x720
Video Compression	H.265+, H.265, H.264+, H.264 Video Compression Standards
Lens	2.7mm ~ 13.5mm, Automatic Focusing & Motorised Zoom Lens (Acceptance of ± 10%)
Optical Zoom	5x Optical Motorised Zoom
Digital Zoom	16x Digital Zoom
Adjustment Angle	3 Axis
Iris	Fixed Iris
Viewing Angle	100.4°~26.8°
Bandwidth	32Kbps ~ 8192Kbps
Signal/ Noise Ratio	>60dB
Automatic Gain Control	Automatic Gain Control, White Balance, Electronic Day & Night (ICR)
Ethernet	Ethernet: 1*RJ45 10M/100M
Privacy Masking	up to (4 Areas, Rectangular)
Wide Dynamic range	120dB WDR
Advanced Function	BLC, HLC, 2D DNR, 3D DNR, AWB, IP Address Filtering, AGC
Protocol	TCP/IP, HTTP, FTP, DHCP, DNS, DDNS, MULTICAST, IPV4, NTP, UDP, Telnet
Event Trigger	Motion Detection, Mask Alarm, IP Address Conflict
Image Setting	Brightness, Contrast, Saturation, Sharpness, Image Rotation
Image Enhancement Function	AWB, AGC
Video Analytics	Tripwire, Perimeter
ONVIF	ONVIF Profile S, T , G
Access	on Android, Windows Phone
Users	8 Users simultaneously
On-board storage	up to 256GB Micro SD
Power Consumption	7.5W Max, 9W Max with IR on
Housing	Dome Camera
Power Parameters	PoE (802.3af)/ DC 12V±10%
Temperature	-40°C~65°C, Less than 95% RH

<sup>\*</sup>Due to continuous product development, the specifications may change without prior notice.
\*\*Product image(s) are for illustrative purposes only and may differ from the actual product.



## Corporate Office:

A-66, Sector-4, Noida, District Gautam Buddha Nagar, U.P., India - 201301