







## Technical Specification GCAT6I

## Cat6 Cable

Cate 6 cable conforming to ANSI/TIA/EIA-568 C.2 latest or ISO/IEC:11801 latest	Yes
Cable category: Category 6 Unshielded/Unshielded twisted pair or Category 6 Foiled/Unshileded twisted pair or Category 6 Shielded /Foiled Twisted Pair	CAT6 U/UTP
Cable colour	Grey
Conductor diameter	0.57 mm (23 AWG)
Conductor count (in Nos.,)	8
Length of cable in a bundle (Mtrs)	100 mtrs.

Maximum DC resistance - in Ohm/Km	Max. 100 Ohm/Km
Conductor Material	Bare Copper
Conductor Insulation Material	Polyethylene
Cable jacket material	Fire retardant PVC
Conductor stranding	Solid
Cable should have internal cross separator	Yes
Storage temperature range	minus 20 degree C to plus 60 degree C
Operating temperature range	minus 20 degree C to plus 60 degree C
UL Marking on Cable	No

For Sales ►

Contact: 0 85888 39434 Email: sales@globusinfocom.com



## **Globus Infocom Limited**

A 66, Sector-4, Noida - 201301 (U.P.) Email: info@globusinfocom.com Website: www.globusinfocom.com

Toll Free: 1800-200-4398



<sup>\*</sup>Due to continuous product development, the specifications may change without prior notice.

<sup>\*\*</sup>Product image(s) are for illustrative purposes only and may differ from the actual product.