



Globus Audio System

Two Way PA Speaker

MODEL: GIL 80W



Speaker Type	Main Speaker
Enclosure	Polycarbonate
Amplification Method	Passive Speaker
Mounting	Wall Mount
Woofer and Tweeter	8''woofer+3''tweeter
Configuration	Two Way
Number of Speaker	Two
Frequency Response	20-20,000 Hz
Low Frequency Unit	4 Inch
High Frequency Unit	1 inch
Sound Pressure Level (1W/1m)	45 dB
Coverage Pattern	3D surround sound
Sound Pressure Level	70 dB Max.
Nominal Impedance	8 Ohm
Speaker Port	Sealed Enclosure
Connectors	3.5mm
Mounting	Wall Mount
Dimension	990W x 93H x 70D mm
Weight	3Kg.
Power Rating	80 Watt
AC Power Input	230V ~ 50/60 Hz
LED Indicator	Available

*Due to continuous product development, the specifications may change without prior notice.

**Product image(s) are for illustrative purposes only and may differ from the actual product.



Corporate Office:

A-65, Sector-4, Noida, District Gautam Buddha Nagar, U.P., India - 201301

☎ 0120-4051700/800 ☎ 0120-4051827 ✉ info@globusinfocom.com

☎ For Sales: 0 85888 39434 🌐 www.globusinfocom.com