



Impact Series 250 Watt Audio Amplifier MODEL GIL-AA-250

Amplifier	Class D
Rated Power	250 W
Impedance	MIC input: 5mV / 600Ω balanced; AUX1,2 input: 350mV / 10KΩ unbalanced RCA connection terminal
Mic Input	Minimum 4 input
Line Input	2 input
Output	MIX OUT: 1000mV / 470Ω unbalanced RCA connector
Tone	Bass: ± 10dB at 100Hz; Treble: ± 10dB at 10KHz
Frequency Response	80Hz ~16KHz (+ 1dB, -3dB)
SNR	MIC1,2,3: 66dB; AUX1,2: 85dB
THD	< 0.05% (at 1KHz, 1/3 rated power)
Mute Function	MIC 1 is prior to MIC2-4, AUX1-2 audio input; EMC is prior to all audio inputs
Channel Crosstalk Attenuation	≥50dB
Heat Dissipation	Side-in and rear-out forced fan cooling; fan starts auto device is turned on; infinitely variable speed
Protection	Overheat protection, overcurrent protection, short circuit protection
Power Supply	AC ~ 220V / 50Hz
Power Consumption	300W

*Due to continuous product development, the specifications may change without prior notice.

**Product image(s) are for illustrative purposes only and may differ from the actual product.



Corporate Office:

A-66, Sector-4, Noida, District Gautam Buddha Nagar, U.P., India - 201301

☎ 0120-4051700/800 ☎ 0120-4051827 ✉ info@globusinfocom.com

☎ For Sales: 0 85888 39434 🌐 www.globusinfocom.com