



Power Amplifier

Compact, Excellent and Efficiency

MODEL: GPADC-M2



Power Amplifier	
Audio Amplifier	100 + 100 dual Chanel
Frequency Response	20 Hz - 20 kHz, +0/-1 dB (at 1 watt)
THD	<0.5%, 20 Hz - 20 kHz
Intermodulation Distortion	<0.35% (60 Hz and 7 kHz at 4:1 from full rated output to -30 dB)
Slew Rate	>10V/us
Voltage Gain	31 dB
Damping Factor	(8 ohms, 10 Hz to 400 Hz) >200
Signal To Noise Ratio	>100 dB
Crosstalk	20 Hz to 1 kHz -75 dB, -59 dB
Input Sensitivity	(for full rated power at 8 ohms) 0.775V or 1.4V
Input Impedance	(nominal balanced, unbalanced) 20k Ω , 10k

*Due to continuous product development, the specifications may change without prior notice.

**Product image(s) are for illustrative purposes only and may differ from the actual product.



Corporate Office:

A-66, Sector-4, Noida, District Gautam Buddha Nagar, U.P., India - 201301

☎ 0120-4051700/800 ☎ 0120-4051827 ✉ info@globusinfocom.com

📱 For Sales: 0 85888 39434 🌐 www.globusinfocom.com