

Interactive Display

Globus Interactive Displays are advanced next-generation touch displays that deliver crisp visuals, enhanced interactivity and seamless performance



Model : GS18-10
100 Inches



Android 14



Octa-Core
Processor



8GB



128 GB



Anti-Glare
Screen



AI-enabled
Whiteboard
Application



Split
Screen



Wireless
Screen
Sharing

**Ideal for classrooms,
meeting rooms &
training rooms**

* Product images are only for illustration purposes and may be different from the actual product

Registered and Corporate Office: A-66, Sector-4, Noida, District Gautam Buddha Nagar, Uttar Pradesh, India – 201301
Email: sales@globusinfocom.com | Mobile: +91 8588839434 | Website: www.globusinfocom.com

Specifications



Model No.	GS18-10
DISPLAY	
Display Technology	In-Plane Switching (IPS)
Display Type	Anti-Glare LCD with Direct-lit LED
Contrast Ratio	2000:1
Display Panel Size, Diagonal (in Inches)	100
Display Resolution (H x V) (in Pixels)	4K UHD - 3840 x 2160
Display Brightness (in Nits)	450
Display Aspect Ratio	16:9
View Angle (in Degree)	178 by 178
Minimum Panel Life (in Hours)	50000
TOUCH SCREEN	
Touch Technology	Infrared (IR)
Touch Points (in Number)	40
Response Time (in ms)	4
Tempered Glass	4.0 mm
CPU	
Cores	8
Memory (in GB)	8
SSD Storage Capacity (in GB)	128
Pre-Install Software (OS)	Android 14
Open pluggable Specification (OPS) Slot	Available
HARDWARE	
Speakers (in Watts)	50 (25 x 2)
PORTS	
Input	HDMI-In x 3, DP-In x 1, VGA-In x 1, VGA Audio-In x 1, Mic-In x 1, RJ45-In x 1, RS232-In x 1, TF Card slot x 1
Output	HDMI-Out x 1, Coaxial x 1, Earphone x 1, RJ45-Out x 1
USB Ports	USB 3.0 Type A x 5, USB 2.0 Type A x 1, USB Type C x 2, USB 3.0 Touch x 2
CONNECTIVITY	
Bluetooth Version	5.3
Wi-Fi Connectivity	Wifi 6E (802.11 ax)
POWER SUPPLY	
Power Supply	100-240 V , AC
AC Frequency (in Hz)	50
Max. Power Consumption (in Watts)	335
ACCESSORIES	
Electronic Pen or Stylus Each Panel	2
Installation Kit for each Panel	User Manual, HDMI cable, Installation Manual, Remote Control with battery, Power Cord, USB Cable
OPERATING CONDITIONS	
Operating Temperature Range (in °C)	0 - 40
Operating Humidity (in %)	10 - 90

Registered and Corporate Office:

A-66, Sector-4, Noida, District Gautam Buddha Nagar, Uttar Pradesh, India – 201301

Email : sales@globusinfocom.com | Mobile : +91- 8588839434

