

# Interactive Display

75 inches

Globus Interactive Displays are advanced next-generation touch displays that deliver crisp visuals, enhanced interactivity and seamless performance



## Key Specs & Features



Android  
14



Quad Core  
Processor



8 GB




64 GB



Anti-Glare  
Screen



AI-enabled  
whiteboard  
application



Split-Screen



Gesture Control

Ideal for classrooms,  
meeting rooms and  
training rooms

## Specifications

<b>Model No</b>	<b>IDS7A-1</b>
Display Resolution (in Pixels)	4K UHD - 3840 x 2160
Display Brightness (in Nits)	350
Contrast Ratio	1100:1
Display Panel Size (Diagonal - in Inches)	75
Smart Eye Protection	Yes
Minimum Panel Life (in Hours)	50000
<b>Touch Screen</b>	
Touch Interface	Touch Sensitive as well as Pen Driven
Touch Technology	Infrared (IR)
Number of Touch Points	20
Response Time (in millisecond)	8
Tempered Glass	3 mm, Anti-glare coating
Annotation Software	Yes
<b>CPU</b>	
Processor	Quad Core
Memory (RAM)	8
SSD Storage Capacity (in GB)	64
Pre-Install Software (OS)	Android 14
Provision of Slot for Open pluggable Specification (OPS)	Yes
<b>Ports</b>	
Input HDMI	2
RJ-45	1
USB Type-C	1
USB 3.0	3
<b>Additional Hardware</b>	
Speaker Power (in Watts)	40 (20 x 2)
<b>Connectivity</b>	
Bluetooth Version	5.0
Wi-Fi Connectivity	Wi-fi 5 (2.4 & 5Ghz)
<b>Other Feature</b>	

\* Due to continuous product development, the specifications may change without prior notice  
 \*\* Product images are for illustration purpose only and may be different from the actual product

Whiteboard Interactive Software (Android) Features	Multi-touch writing (multiple users simultaneously), Pen, marker, highlighter tools, Adjustable pen thickness and colors, Eraser (finger, pen-end, or tool-based), Lasso/select tool to move or resize content, Geometrical Tools
Wireless screen sharing	Share/mirror the content of an external device wirelessly on the interactive panel
<b>Power Supply</b>	
Power Supply	100-240 V, AC
AC Frequency (in Hz)	50
Power Consumption (in Watts)	350
<b>Accessories</b>	
Mounting	Wall Mount
Number of Electronic Pen or Stylus Each Panel	2
Remote	1
HDMI Cable (1.5 Meter)	1
Power Cable (1.5 Meter)	1
USB A to B cable (1.5 Meter)	1
<b>Operating Conditions</b>	
Operating Temperature (in Degree Celsius)	0 - 40
Operating Humidity (in Percentage)	10 to 90

\* Due to continuous product development, the specifications may change without prior notice  
 \*\* Product images are for illustration purpose only and may be different from the actual product