



## Impact Series 100-Watt Audio Amplifier MODEL: IMPACT ADCS 15

Model	IMPACT ADCS 15
Technology	Class-D
Frequency Response	( $\pm 3$ dB): 20 Hz - 20 kHz
Signal/Noise	> 90 dB
THD	THD+N (@ 1 kHz): < 0.1% (1/2 Rated Power)
Crosstalk (@ 1 kHz)	> 70 dB
Power supply	100~240V AC / 50~60Hz
RMS/AES Power Handling	8 $\Omega$ Stereo: 4 x 50W, 8 $\Omega$ Bridge: 2 x 200 W, 4 $\Omega$ Stereo: 4 x 100W
Power consumption	200 W
Standby mode	5W
Inputs	
Sensitivity	0 dB (1V RMS)
Connector	3-pin XLR female
Impedance	12 k $\Omega$ balanced
Cooling	Colling fan
Operating temperature	0° ~ 40° @ 95% Humidity
Output port	2-pin Euro Terminal Block (Pitch - 5.08 mm)
Protection	DC Short circuit, Overheating, Over load, Signal limiting

\*Due to continuous product development, the specifications may change without prior notice.

\*\*Product image(s) are for illustrative purposes only and may differ from the actual product.



Corporate Office:

A-66, Sector-4, Noida, District Gautam Buddha Nagar, U.P., India - 201301

☎ 0120-4051700/800 ☎ 0120-4051827 ✉ info@globusinfocom.com

☎ For Sales: 0 85888 39434 🌐 www.globusinfocom.com