



Impact Series 30-Watt Ceiling Speaker MODEL: ImpactCMS30

Model	ImpactCMS30
Power Rating	30 Watts
Coverage Angle	120° conical
Directive Factor and Index	7.6 and 8.1 dB
Drivers	LF Driver: 100 mm (4 in), HF Driver: 19 mm (3/4 in)
Frequency Range (-10dB)	74 Hz – 20 kHz
Impedance	8 ohms (in direct/bypass setting)
Crossover Network	12 dB/oct (2nd order) low-pass to LF driver, 12 dB/oct (2nd order) high-pass to HF driver
Frequency Response (± 3 dB)	100 Hz – 20 kHz
Sensitivity	87 dB (1kHz - 16 kHz)
Transform Taps	25 W, 12.5 W, 6.3 W @ 70V or 100V (plus 3.2 W @ 70V only)
Maximum SPL (1m)	101 dB (low-impedance, 108 dB peak), 101 dB (top 70V/100V tap)

*Due to continuous product development, the specifications may change without prior notice.

**Product image(s) are for illustrative purposes only and may differ from the actual product.



Corporate Office:

A-66, Sector-4, Noida, District Gautam Buddha Nagar, U.P., India - 201301

☎ 0120-4051700/800 ☎ 0120-4051827 ✉ info@globusinfocom.com

☎ For Sales: 0 85888 39434 🌐 www.globusinfocom.com