



Omnidirectional Ceiling Microphone

MODEL: - Impact GOM-02

| Ceiling Microphone | |
|--------------------------|--|
| Audio Pickup pattern | 360° Omnidirectional |
| Audio Pickup Range | 8 Meter Radius |
| Digital microphone array | Built-in 7 microphone connected in arrays to form a Omnidirectional mic |
| Sensitivity | -26 dBFS |
| SNR | 64 dB(A) |
| Frequency Response | 20Hz - 16kHz |
| Sampling Rate | 32K sampling, High Definition Broadband Audio |
| USB Protocol | Support UAC |
| Audio Algorithms | 3A algorithm (AEC, AGC & ANS) to provide Cleared Audio experience |
| Audio Features | Intelligent noise reduction, echo cancellation and reverberation suppression to ensure clear sound quality and comfortable communication |
| Plug & Play | USB2.0 and 3.5 mm audio interface with debug-free design to provide plug and play solution, dual-mode (digital, analog) output |
| Intelligent voice Pickup | Adaptive blind beamforming with automatic speaker alignment & speech reinforcement, to prevent interference and to keep speech clear |
| Input/Output Interface | 1 x 3.5mm Line In, 2 x 3.5mm Line Out, 1 x USB |
| USB Interface | UAC 1.0 protocol, audio data communications, software upgrade and parameter configuration |
| Power | USB DC5V |
| Certifications | CE & RoHS |



Corporate Office:

A-66, Sector-4, Noida, District Gautam Buddha Nagar, U.P., India - 201301

☎ 0120-4051700/800 🖨 0120-4051827 ✉

📱 For Sales: 0 85888 39434 🌐