



## Impact Series

### Wireless Dual Microphone with Receiver

MODEL: IMPACT GWTM02

Model	IMPACT GWTM02
RF Output Power	Max.10 mW
Carrier Frequency Range	692 - 669 MHz
Modulation Mode	FM
Power	3V (2 x 1.5V AA Pencil Cells included)
Microphone Element	Dynamic, Cardioid
Frequency Stability	$\pm 0.005\%$
Power On/Off Switch	Yes
Frequency Response	50 - 15,000 Hz
Channel Frequency Display	Available
Current Consumption	< 150 mA
Receiver	
Dynamic Range	> 90dB
Controls	On/Off Switch, Volume Controls, Channel A & B.
Power	220V-240V AC 50Hz, AC adapter
Frequency Response	50 - 15,000 Hz
Capacity	Support 2 Handheld Transmitters (Mic) and both can talk simultaneously.
Audio output	Bal. 0 dBu, Unbal. -10 dBu
S/N Ratio	> 100 dB
Indicator	LEDs for Audio Signal & RF, Channel Frequency Display
Distortion	$\leq 1\%$

\*Due to continuous product development, the specifications may change without prior notice.

\*\*Product image(s) are for illustrative purposes only and may differ from the actual product.



Corporate Office:

A-66, Sector-4, Noida, District Gautam Buddha Nagar, U.P., India - 201301

☎ 0120-4051700/800 ☎ 0120-4051827 ✉ info@globusinfocom.com

☎ For Sales: 0 85888 39434 🌐 www.globusinfocom.com