Nationwide Sales & Service Presence





Corporate Office: A-66, Sector-4, Noida, District Gautam Budh Nagar, Uttar Pradesh - 201301, India | Phone: +91-120-4051700, 4051800 Email: info@globusinfocom.com | www.globusinfocom.com



Digital Projectors

Short Throw Projector (Impact Series) Impact-SWV5

Globus Short Throw Digital Projector is equipped with superior picture quality, long-life and reliability to amplify any lesson, meeting or seminar with vivid colours, bold graphics and razor-sharp clarity. Our short throw projectors work on DLP technology for high-end and reliable performance.









nary Projector Globus Digital Projector


High Luminosity and Amazing Colour Accuracy

DLP technology produces bright and vivid images with amazing colour accuracy even in rooms with high ambient conditions. Enhance your presentation/classroom or meeting sessions with its high luminosity.

Reduced Shadow Interference

With our Short Throw Projectors, interfering shadows or glare won't be a hindrance for your presentation, seminar, meeting or classroom session. It is equipped with a throw ratio as low as 0.69 that allows you to project a large screen even from a very short distance.





Inbuilt Speaker

Users can enjoy playing multimedia files like videos, animations, etc. on our Short Throw Projector with an inbuilt sound output. No hassles of connecting an external audio output device. It comes with an inbuilt 10W speaker for high fidelity sound output.

Advanced Energy Saving Features

Our projectors deliver long-term, maintenance-free operation owing to its long lamp life reducing the total cost of ownership (TCO) for the users. The Economy Mode lets users extend the lamp life by optimizing image brightness accordingly.



Technical Specification

Short Throw Projectors (Impact Series)

Model	Impact-SWV5
Projection System	0.55" 1080p
Technology	One Chip DLP
Display Color	1.07 Billion Colors
Native Resolution	1280 x 800 WXGA
Resolution Support	VGA (640 x 480) to Full HD (1280 x 800)
Brightness	3600 ANSI Lumens
Contrast Ratio	22000 : 1
Lens	F=2.6-2.78, f=10.2-12.24mm
Projection Offset	105% ±5%
Light Source Type	DLP
Light Source Life (Normal Mode)	5000 Hours
Image Size	30"-300"
Optical Zoom	110%
Aspect Ratio (Native and Supported)	4:3, 16:9
Throw Ratio	0.69-0.83
Throw Distance	0.9m-2.2m (100"@1.5m)
Ports	HDMI x 1, Video In (RCA) x 1 (composite video), Audio In x 1, RGB Analog In x 1, Audio Out x 1, RGB Ana Out x 1
Keystone Adjustment	Yes, ±20°Vertical
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility	NTSC, PAL, SECAM
Horizontal Frequency	15K-102KHz
Vertical Scan Rate	23-120Hz
Lamp Watt	310 W
Inbuilt Speaker	20W x 1
Audible Noise	32dB (Standard); 24db (Eco Mode)
Power Supply	100 - 240V ±10%, 50/60 Hz AC
Power Consumption	Normal: 270W; Standby: <0.5W
Operating Temperature	0° C to 40° C, 0-90% RH
Accessories	Power cable, VGA cable, remote control, user manual CD, Wall Mount Kit
Special Features	Auto Power On/ Off, Sleep timer, Power Saving, Presentation Timer, Password Protection, 3D Blu-ray, 3D ready, Audio Pass Through, Keypad Lock, wireless screen share through dongle, presenter device

^{*}Due to continuous product development, the specifications may change without prior notice.

**Product image(s) are for illustrative purposes only and may differ from the actual product.