All Products & Solutions available on GeM Government e Marketplace

4K 12x PTZ Camera

Delivering intelligent pan, tilt and zoom with crystal-clear video for a seamless, AI-powered professional video conferencing experience.

Model : ImpactVC124K

- AI Presenter Tracking
- Auto Framing mode
- High Resolution & Picture Clarity
- Presets Available on IR Remote
- 350° Horizontal and 180° Vertical Rotation
- Optical Zoom

Ideal for boardrooms, meeting rooms & training rooms

* Product images are only for illustration purpose and may differ from the actual product

Registered and Corporate Office: A-66, Sector-4, Noida, District Gautam Buddha Nagar, Uttar Pradesh, India - 201301 Email: sales@globusinfocom.com | Mobile: +91 8588839434 www.globusinfocom.com

Specifications

Model	ImpactVC124K
Parameter	**Specification**
Sensor	Sony 1/2.8" CMOS Sensor
Effective Pixels	8.29 MP
Aperture	F1.8 - 3.0
Lens	f=3.4mm ~ 40.9mm
Horizontal Field-of-View	70° ~ 7.6°
Vertical Field-of-View	40° ~ 4.3°
Diagonal Field-of-View	76° ~ 8.7°
Video Format	HDMI: 3840x2160@30/25, 2560x1440@60, 1920x1080@60/50/30/25, 1280x720@60/50 USB: Max to 3840x2160@30
Optical Zoom	12x
Digital Zoom	8x
AI-Tracking Modes	Presenter Tracking, Auto Framing
Video Encoding Format	H.264, H.265, MJPEG, YUY2
Video S/N	≥50dB
Digital Noise Reduction	2D and 3D Digital Reduction
Focus	Auto/Manual
Exposure	Auto/Manual
Pan & Tilt Parameters	
Horizontal Rotation	350° (-175° to +175°)
Vertical Rotation	180° (-90° to +90°)
Number of presets	User can set up to 255 presets (10 presets on IR remote)
Input/Output Interface	
Video Interfaces	HDMI, USB 3.0, RJ45
LAN	10M/100M, Supports PoE IEEE802.3 af
Video Streams	Main Stream: 1920x1080 (Max), Sub Stream: 1280x720 (Max)
Network Protocol	RTSP, RTMP, VISCA Over IP, ONVIF
Control Protocol	VISCA/PELCO-D/PELCO-P
Control Interface	RS232(input), RS485, USB3.0 (UVC1.1), RJ45
General	
Compatible Operating Systems	Windows/Android/Mac OS/Linux
Input Voltage	DC 12V
Current Consumption	2A (Max)
Power Consumption	24W (Max)
Operating Temperature	0° to 40° degrees celsius
Storage Temperature	-20° to 60° degrees celsius

Registered and Corporate Office:
A-66, Sector-4, Noida, District Gautam Buddha Nagar, Uttar Pradesh, India – 201301
Email : sales@globusinfocom.com I Mobile : +91- 8588839434, www.globusinfocom.com

GLOBUS INFOCOM LIMITED

POSSIBILITIES UNLIMITED
CELEBRATING 25 GLORIOUS YEARS OF INNOVATION

Registered and Corporate Office:
A-66, Sector-4, Noida, District Gautam Buddha Nagar, Uttar Pradesh, India – 201301
Email : sales@globusinfocom.com I Mobile : +91- 8588839434, www.globusinfocom.com