



Impact Series

Video Bar

Model No - IMPACT VC6AIO



Video Bar		IMPACT VC6AIO
Loudspeaker Array		
Configuration	Ported enclosure, stereo loudspeakers	
Frequency Response (−10 dB)	100Hz – 16KHz	
Amplifier Power	10W per channel	
SPL	89 dB	
Microphone Array		
Configuration	4 microphones	
Frequency Response	100Hz – 16KHz	
Pickup Range	6.0 m	
Technology	Static and adaptive dynamic beamforming, stereo acoustic echo cancellation (AEC), digital noise suppression	
Field of View (FOV)	120° diagonal × 110° horizontal × 75° vertical	
Image Sensor	8 MP	
Focus Distance	0.5 m	
Lens	Up to 5x digital zoom, with detachable camera privacy cover	
Processing	Automatic white balance, automatic brightness, digital noise reduction	
USB Device	Video Class (UVC) v1.1	
Positioning	Auto framing capability or manual pan-tilt-zoom (PTZ) with 3 configurable presets	
Supported Video Resolutions	UHD 2160p (4K), 1080p, 720p, 960×480, 848×480, 640×480, 640×360, 432×240 (30 fps)	
Video Encoding:	H.264, M-JPEG	
Connections and Ports		
USB	USB Type-C	
Bluetooth	Bluetooth 4.2	
Display	1x HDMI	
Network: Wired	RJ-45, 1 Gbps Ethernet	
Wireless	Wi-Fi 802.11ac	
Audio	Stereo 3.5 mm (1/8 in) input	
General Purpose	2-pin Euro block general-purpose input	
Power	110 – 240 VAC, 50/60 Hz, 1.5 A max	
Output	24 VDC, 1.875 A	
Control/Configuration:	Setting/Control/Configuration software (available for Windows and macOS or via web browser)	
Operating System	Windows 10, macOS 10.10	

*Due to continuous product development, the specifications may change without prior notice.

**Product image(s) are for illustrative purposes only and may differ from the actual product.



Corporate Office:

A-66, Sector-4, Noida, District Gautam Buddha Nagar, U.P., India - 201301

☎ 0120-4051700/800 ☎ 0120-4051827 ✉ info@globusinfocom.com

📱 For Sales: 0 85888 39434 🌐 www.globusinfocom.com