

Application Areas



Educational Institutes



Board Rooms



Training Rooms



Conference Rooms

and many more..

Nationwide Sales & Service Presence



Corporate Office: A-65, Sector-4, Noida, District Gautam Budh Nagar,
Uttar Pradesh - 201301, India | **Phone:** +91-120-4051700, 4051800
Email: info@globusinfocom.com | **www.globusinfocom.com**



Video Conferencing Full HD PTZ Camera

ImpactWM2

Perfect need-based camera catering to the conferencing requirements of huddle rooms, conference rooms, auditoriums, etc. of varied dimensions and sizes. It offers Full HD resolution also provide crystal clear image even under low light conditions.

Communication
made
Impactful





High Resolution and Optimum Zoom

Comes with a superior and crystal-clear video resolution of 1080 p which supports powerful zoom. It brings a vast range of clarity to your video conferencing while increasing the communication capability.

Design & Construction

Solid and rugged video conferencing which imparts a premium look to your experience. It can be mounted on the top panel/monitor for better space management.



High Quality Images in Low Light

The CMOS sensor accounts for exception performance and high quality images even in low light conditions due to its high signal-to noise ratio.

Auto White Balance and Brightness Control

Adjusts brightness and white balance automatically to optimize video quality. This feature helps the user attain a flawless video conferencing output.



Technical Specification

Full HD PTZ Video Conferencing Camera

Model	ImpactWM2
Camera Resolution	1080p (Full HD)
Sensor	1/2.8" CMOS Sensor
Effective Pixels	2 MP
Scanning Mode	Progressive
Zoom	Available
Minimal Illumination	0.5 Lux @ (F1.8, AGC ON)
Shutter	1/30s ~ 1/10000s
White Balance	Auto/ Indoor/Outdoor/One Push/Manual
Backlight Compensation	Support
Digital Noise Reduction	2D/3D Digital Noise Reduction
Field of View	70°
PAN Range	180°
Tilt Range	50°
Anti-Flickering	Supported
Built in Microphone	Available with upto 5 feet Audio Pickup
Video System	USB: 1080P@30fps, 1080P@25fps, 720P@60fps
Compression	Software for Video Recording using H.264

Feature	
System Supported	Windows, Mac OS, Linux

Port Interface	
Connectivity	1x USB

Generic Specification	
Input Voltage	DC 12V
Current Consumption	12V - 1.0A(MAX)
Operating Temperature	0°C ~ 40°C
Storage Temperature	-10°C ~ 60°C
Accessories	Remote control, User Manual, USB cable
Power Consumption	12W (Max)

**Product image(s) are for illustrative purposes only and may differ from the actual product

*Due to continuous product development, the specifications may change without prior notice.