

# Video Conferencing Full HD PTZ Camera



Perfect need-based camera catering to the conferencing requirements of huddle rooms, conference rooms, auditoriums, etc. of varied dimensions and sizes. It offers Full HD resolution also provide crystal clear image even under low light conditions.

## Key Features

- Feasible connectivity
- Collaborate & Share Ideas
- Manage Your Conference from Anywhere



High Quality  
Video Conferencing  
Experience



CMOS Sensor



Safe & Secure  
Conferencing



Remote Control for  
high-speed communications,



Multiple  
connectivity ports



**Conference Rooms**



**Training Rooms.**

\* Due to continuous product development, the specifications may change without prior notice  
\*\* Product images are for illustration purpose only and may be different from the actual product



Video Conferencing Camera	ImpactVC202K
Sensor	1/2.8", CMOS, Effective Pixel: 2 MP
Optical Zoom	20x
Horizontal Field-of-View	50 degrees(W) ~ 3 degrees(T)
Vertical Field-of-View	28 degrees(W) ~ 1.8 degrees(T)
Diagonal Field-of-View	58 degrees(W) ~ 3.5 degrees(T)
Horizontal Rotation	350° (-175° to +175°)
Vertical Rotation Range	180° (-90° to +90°)
Number of presets	User can set up to 255 presets (10 presets on IR remote)
Video S/N	≥50dB
Video Signals	1080p@60/50/30/25fps, 720p@60/50/30/25fps
Video Encoding Format	H.265, H.264, MJPEG, YUY2
Input/Output Interface	
Control Interface	USB 3.0, RS-232 (Input), RS485
Video Output	USB 3.0
General	
Compatible Operating Systems	Windows/Android/Mac OS/Linux
Input Voltage	DC 12V
Current Consumption	2A (Max)
Power Consumption	24W (Max)
Operating Temperature	0° to 40° degrees celsius
Storage Temperature	-20° to 60° degrees celsius